

TITLE OF THE INVENTION
INFORMATION SEARCH METHOD,
INFORMATION SEARCH APPARATUS, AND STORAGE MEDIUM

5 FIELD OF THE INVENTION

The present invention relates to an information search method of accurately searching for additional information (e.g., advertisement information) more desired by a user.

10

BACKGROUND OF THE INVENTION

Along with the recent development of communication technology, the following methods have been used to provide information to users.

15

- 1: Internet Web
- 2: Internet push-type news distribution service
- 3: FAX information extraction service
- 4: Sending material requesting coupons attached to newspapers/magazines

20

- 5: Inquiry by free dials
- 6: Sending material requesting postcards

As portable information terminals are being widely used, information providing services using character information are becoming active. However, since a
25 portable terminal has a limited display ability in size, colors, and resolution, a detail information providing

service capable of compensating for it need be realized.

The above methods are conventionally used to acquire detail information, though they have limitations.

Methods 1 and 2 are limited to PC or terminal
5 users well versed in the Internet environment, and it is also time-consuming to find a URL necessary for access to desired information. Method 3 is limited to FAX users. In addition, the print ability (monochrome printing and print preview) is limited, and the output cost
10 (telephone charge or cost of paper) is for the users to bear. Methods 4, 5, and 6 are available for many and unspecified users. However, a user can acquire information several hours or several days after the request. The information provider side must also prepare
15 a physical request processing system, resulting in an increase in information providing cost.

Sub D11 The information provider side wants a user to have an interest in, e.g., advertisement information. In fact, advertisement information is not always indispensable
20 for the user. It is preferable to appropriately provide such dispensable information timely because the user is not displeased with the advertisement, and additionally, information on the provide side is transmitted to the user.

25

SUMMARY OF THE INVENTION

09547397-044100

In order to achieve the above object, according to the present invention, there is provided a search method of searching for output information strongly related to input information from a plurality of candidate

5 information, characterized by comprising:

the assignment step of assigning in advance one or a plurality of keywords typically representing information to the input information and each of the plurality of candidate information, and a weight value
10 set in association with information to each keyword;

the arithmetic step of executing a predetermined arithmetic operation for the weight value of each keyword of the input information and the weight value of each keyword of each of the plurality of candidate
15 information; and

the selection step of selecting target output information from the plurality of candidate information on the basis of a sum value of arithmetic results obtained by performing the predetermined arithmetic
20 operation for substantially all keywords of each candidate information in the arithmetic step.

The sum value obtained for each of the plurality of candidate information means the relation of the candidate information to the input information.

25 According to the preferred aspect of the present invention, the predetermined arithmetic operation is

09547397-041100

multiplication of the weight values, and information having a larger sum value of the arithmetic results is selected as the output information.

Pieces of information related to each other may
5 have a relation in opposite directions. For example, information associated with a funeral home and information associated with a wedding ceremony hall are related to each other because the both are associated with ceremonial occasions, although they induce
10 exclusive values.

According to another preferred aspect of the present invention, the weight value has a sign determined for each keyword in advance, and when the result of the predetermined arithmetic operation for the
15 weight values of a set of keywords has a relatively large positive value, it is determined that the relation is strong. By attaching signs to two pieces of information related to each other in opposite directions, the pieces of information can be appropriately
20 quantified.

According to still another preferred aspect of the present invention, the method is characterized by further comprising:

the input step of inputting the input information
25 from a predetermined terminal;

the first storage step of storing contents of the

plurality of candidate information in an information provider server; and

the second storage step of storing the keywords of each of the plurality of candidate information and the
5 weight values of the keywords in a management server.

To positively collect only information more strongly related to the user side does not make the user displeased. According to still another aspect of the present invention, there is also provided a search
10 method of searching for output information strongly related to input information from a plurality of candidate information, characterized by comprising:

the registration step of registering in advance one or a plurality of keywords representing selectivity
15 to the input information; and

the selection step of selecting, as the output information, information having a larger number of keywords having values close to the value of the one or the plurality of keywords from the plurality of
20 candidate information.

According to still another preferred aspect of the present invention, the method further comprises:

the first storage step of storing the plurality of candidate information in an information provider server;
25 and

the second storage step of storing the one or the

plurality of keywords representing selectivity to the input information in a management server.

According to still another preferred aspect of the present invention, the input information is specific
5 information corresponding to a predetermined code input by a user, and each of the plurality of candidate information is information to be attached to the specific information and presented to the user.

The above object can also be achieved by a search
10 method of searching for output information strongly related to input information from a plurality of candidate information, characterized by comprising:

the assignment step of assigning in advance one or a plurality of information keywords typically
15 representing information to the input information and each of the plurality of candidate information, and a weight value set in association with information to each information keyword;

the registration step of registering in advance
20 one or a plurality of user keywords representing selectivity to the input information;

the calculation step of executing a predetermined arithmetic operation for the weight value of each of the plurality of information keywords and the weight value
25 of each information keyword of each of the plurality of candidate information and calculating a sum value of

arithmetic results obtained by performing the predetermined arithmetic operation for substantially all information keywords of each candidate information in the arithmetic step;

5 the quantification step of quantifying the degree of matching between each keyword of each of the plurality of candidate information and the one or the plurality of user keywords; and

10 the selection step of selecting, as the output information, the largest candidate information from a result obtained by adding quantified values obtained in the quantification step to the sum value.

15 In the method of the present invention, an apparatus keyword of a terminal apparatus for outputting the output information and a weight value of each apparatus keyword are stored in advance, and the weight value of each apparatus keyword is taken into consideration.

20 Other features and advantages of the present invention will be apparent from the following description taken in conjunction with the accompanying drawings, in which like reference characters designate the same or similar parts throughout the figures thereof.

25 BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated

in and constitute a part of the specification,
illustrate embodiments of the invention and, together
with the description, serve to explain the principles of
the invention.

Fig. 1 is a view for explaining the schematic arrangement of a P service system according to an embodiment;

Fig. 2 is a view showing the schematic appearance
of a P service terminal 100 according to this
10 embodiment;

Fig. 3 is a block diagram showing the control arrangement of the P service terminal 100;

Fig. 4 is a view showing the schematic appearance of a portable terminal 400 capable of transmitting a P-code to the P service terminal;

Fig. 5 is a block diagram for explaining the control arrangement of the portable terminal 400;

Fig. 6 is a block diagram showing the schematic arrangement of a P service server 200;

20 Fig. 7 is a view showing a data structure example
of an IP information registration table;

Fig. 8 is a view showing a data structure example of an advertisement information table;

Fig. 9 is a view showing a data structure example
25 of a user information table;

Fig. 10 is a view showing a data structure example

of a mail service P-code table;

Fig. 11 is a view showing a data structure example
of a distribution service P-code table;

Fig. 12 is a view showing a data structure example
5 of a personal information service P-code table;

Fig. 13 is a view showing a data structure example
of a personal information table;

Fig. 14 is a view showing a data structure example
of an owner information table;

10 Fig. 15 is a view showing a data structure example
of a terminal information table;

Fig. 16 is a block diagram showing the typical
arrangement of an IP server 300;

Fig. 17 is a view for explaining the data
15 structure of a P-code used in the P service system
according to this embodiment;

Fig. 18 is a view showing the data structure of a
P-code;

Fig. 19 is a flow chart for explaining the outline
20 of processing by the P service server of this
embodiment;

Fig. 20 is a flow chart for explaining the outline
of processing by the P service server of this
embodiment;

25 Fig. 21 is a flow chart of user registration
processing;

001100 041100 2624560

Fig. 22 is a dialog box for new registration processing;

Fig. 23 is a dialog box corresponding to a "name/address" button 1000;

5 Fig. 24 is a dialog box corresponding to a "password" button 1010;

Fig. 25 is a dialog box corresponding to a "place of employment" button 1020;

10 Fig. 26 is a dialog box corresponding to a "credit card" button 1030;

Fig. 27 is a dialog box corresponding to a "service" button 1040;

Fig. 28 is a dialog box corresponding to a "personal information" button 1050;

15 Fig. 29 is a dialog box corresponding to a "personal information 2" button 1060;

Fig. 30 is a dialog box corresponding to a "desired information" button 1070;

20 Fig. 31 is a dialog box corresponding to a "printing paper" button 1080;

Fig. 32 is a dialog box for registration change processing;

Fig. 33 is a dialog box for password change;

25 Fig. 34 is a flow chart of IP information registration processing;

Fig. 35 is a dialog box for confirming a member;

Fig. 36 is a dialog box for inputting member's password;

Fig. 37 is a dialog box for specifying a nonmember;

5 Fig. 38 is a dialog box for inviting registration of a member;

Fig. 39 is a dialog box for setting charging;

Fig. 40 is a dialog box for designating IP information;

10 Fig. 41 is a dialog box for designating IP information;

Fig. 42 is a dialog box showing a preview window;

Fig. 43 is a dialog box when file transfer progresses;

15 Fig. 44 is a dialog box for setting a property;

Fig. 45 is a dialog box for setting another property;

Fig. 46 is a dialog box for setting still another property;

20 Fig. 47 is a dialog box for setting still another property;

Fig. 48 is a dialog box for confirming a password;

Fig. 49 is a dialog box for setting still another property;

25 Fig. 50 is a dialog box for setting still another property;

Fig. 51 is a dialog box for setting still another property;

Fig. 52A is a dialog box for setting still another property;

5 Fig. 52B is a dialog box for setting still another property;

Fig. 52C is a dialog box for setting still another property;

10 Fig. 53 is a dialog box for displaying the list of input items;

Fig. 54 is a flow chart of advertisement information registration processing;

Fig. 55 is a dialog box for confirming a member;

15 Fig. 56 is a dialog box for inputting a member's password;

Fig. 57 is a dialog box for specifying a nonmember;

Fig. 58 is a dialog box for designating advertisement information;

20 Fig. 59 is as dialog box showing a preview window;

Fig. 60 is a dialog box when file transfer progresses;

Fig. 61 is a dialog box for setting a property;

25 Fig. 62 is a dialog box for setting another property;

Fig. 63 is a dialog box for setting still another

property;

Fig. 64 is a dialog box for setting still another property;

Fig. 65 is a dialog box for setting still another
5 property;

Fig. 66 is a dialog box for setting still another property;

Fig. 67 is a dialog box for setting still another property;

Fig. 68 is a dialog box showing the list of input
10 items;

Fig. 69 is a dialog box for printing registered items;

Fig. 70 is a flow chart for explaining the
15 personal P-code issue procedure in step S111;

Fig. 71 is a flow chart for explaining a procedure
in which the P service server assigns the external code
of a P-code to ^{another}~~another~~ site;
A

Fig. 72 is a view showing the data structure of a
20 P-code use registration table used in this embodiment;

Fig. 73 is a view showing the data structure of a P-code use table;

Fig. 74 is a flow chart for explaining IP-code issue processing;

Fig. 75 is a view showing an example of the
25 display window displayed on a touch panel 104 of the P

service terminal 100 of this embodiment;

Fig. 76 is a view showing another example of the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

5 Fig. 77 is a view showing still another example of the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

Fig. 78 is a view showing still another example of the display window displayed on the touch panel 104 of
10 the P service terminal 100 of this embodiment;

Fig. 79 is a view showing still another example of the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

Fig. 80 is a view showing still another example of
15 the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

Fig. 81 is a view showing still another example of the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

20 Fig. 82 is a view showing still another example of the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

Fig. 83 is a view showing still another example of the display window displayed on the touch panel 104 of
25 the P service terminal 100 of this embodiment;

Fig. 84 is a view showing still another example of

00110 26E4560

the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

Fig. 85 is a view showing still another example of the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

Fig. 86 is a view showing still another example of the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

Fig. 87 is a view showing still another example of the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

Fig. 88 is a view showing still another example of the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

Fig. 89 is a view showing still another example of the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

Fig. 90 is a view showing still another example of the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

Fig. 91 is a view showing still another example of the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

Fig. 92 is a view showing still another example of the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

Fig. 93 is a view showing still another example of the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

Fig. 94 is a view showing still another example of
5 the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

Fig. 95 is a view showing still another example of the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

10 Fig. 96 is a view showing still another example of the display window displayed on the touch panel 104 of the P service terminal 100 of this embodiment;

Fig. 97 is a view showing still another example of the display window displayed on the touch panel 104 of
15 the P service terminal 100 of this embodiment;

Fig. 98A is a flow chart showing a processing flow for executing the information service of this embodiment;

Fig. 98B is a view showing the processing sequence
20 in a service system for executing the information service of this embodiment;

Fig. 99A is a flow chart showing a processing flow for executing the mail service of this embodiment;

Fig. 99B is a view showing the processing sequence
25 in the service system for executing the mail service of this embodiment;

Fig. 100A is a flow chart showing a processing flow for executing the distribution service (reception of registered information) of this embodiment;

Fig. 100B is a view showing the processing
5 sequence in the service system for executing the
distribution service (reception of registered
information) of this embodiment;

Fig. 101A is a flow chart showing a processing
flow for executing the personal information service of
10 this embodiment;

Fig. 101B is a view showing the processing sequence in the service system for executing the personal information service of this embodiment;

Fig. 102A is a flow chart showing a processing
15 flow for executing the distribution service
(registration of information) of this embodiment;

Fig. 102B is a view showing the processing sequence in the service system for executing the distribution service (registration of information) of this embodiment;

Fig. 103A is a flow chart for explaining another form of P-code transmission processing by the portable terminal of this embodiment;

Fig. 103B is a flow chart for explaining a
25 procedure of acquiring IP information, mail data, and
distribution data in the P service server 200 of this

embodiment;

Fig. 104 is a flow chart of advertisement search processing;

Fig. 105A is a view showing an example of a
5 keyword list of IP information;

Fig. 105B is a view showing an example of a keyword list of user registration;

Fig. 105C is a view showing an example of a keyword list of the P service terminal;

10 Fig. 105D is a view showing an example of a highest priority keyword list;

Fig. 105E is a view showing an example of a lowest priority keyword list;

Fig. 106A is a view showing an example of the
15 search result list of an IP information list;

Fig. 106B is a view showing an example of the search result list of a user registration list;

Fig. 106C is a view showing an example of the search result list of a P service terminal list;

20 Fig. 106D is a view showing an example of the search result list of a highest priority list;

Fig. 106E is a view showing an example of the search result list of a lowest priority list;

Fig. 107A is a view showing an example of the
25 search result list of the rearranged IP information list;

Fig. 107B is a view showing an example of the search result list of the rearranged user registration list;

Fig. 107C is a view showing an example of the search result list of the rearranged P service terminal list;

Fig. 107D is a view showing an example of the search result list of the rearranged highest priority list;

Fig. 107E is a view showing an example of the search result list of the rearranged lowest priority list;

Fig. 108 is a flow chart for explaining P-code extraction processing of the portable terminal of this embodiment;

Fig. 109 is a flow chart for explaining automatic P-code extraction processing in step S3113;

Fig. 110 is a flow chart for explaining P-code transmission processing by the portable terminal of this embodiment; and

Fig. 111 is a flow chart for explaining another form of P-code transmission processing by the portable terminal of this embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention

will now be described in detail in accordance with the accompanying drawings.

<System Arrangement>

00547397-041100

A service system (to be referred to as a P service system hereinafter) to be described in this embodiment has a plurality of service terminals (to be referred to as P service terminals hereinafter) installed in shops or stations and a dedicated service server (to be referred to as a P service server hereinafter) connected to the P service terminals. When a code (to be referred to as a P-code hereinafter) in a predetermined form is input from a P service terminal, corresponding information is acquired from the P service server, and the print of necessary information is obtained. Note that designation of a P-code to a P service terminal can be done by unspecified users.

Fig. 1 is a view showing the schematic arrangement of the P service system according to this embodiment. Referring to Fig. 1, reference numeral 100 denotes a P service terminal; and 200, a P service server. The P service terminal 100 communicates with the P service server, acquires information corresponding to a P-code input by a user, and prints the information. Alternatively, image information input in the P service terminal 100 can be uploaded to the P service server.

The P service terminal 100 can be a terminal

installed for public use in a shop, street, or public facility. In this case, the P service terminal 100 does not include a terminal used by only a specific person, e.g., a so-called personal computer used by a person at home.

The P service server 200 issues P-codes corresponding to provided information, registers the P-codes in a P-code database, and manages them. The P service server 200 acquires information corresponding to a P-code input from the P service terminal 100, generates print data, and outputs it to the P service terminal 100.

An information provider server 300 (to be referred to as an IP server hereinafter) is, e.g., a general Internet provider. In response to an information request from the P service server 200, the IP server 300 transmits information (contents) corresponding to the P-code attached to the information request to the P service server 200. Additionally, as will be described later, the P service server 200 sets a plurality of usable P-codes in the IP server 300, and the IP server 300 can uniquely ^{issue}~~issues~~ a P-code in correspondence with information provided from a user terminal within the range of the usable P-codes.

Fig. 1 shows a system in which the P service server 200 and IP server 300 independently function, and

information can be transmitted/received through a communication network. However, a system in which the P service server 200 incorporates the IP server 300, and the function of the IP server is realized by the P
5 service server may be constructed.

When the P-code of information managed on the IP server 300 side is input from the P service terminal 100, the P service server 200 finds a corresponding IP server from the P-code and transmits the P-code to this IP
10 server to request information.

A portable terminal 400 is, e.g., a portable telephone. The IP server 300 notifies a P service terminal user (to be simply referred to as a user hereinafter) of a P-code informed from the P service
15 server 200 by inserting the P-code on media 610 such as newspapers and magazines or describing the P-code in mail information transmitted to the user's portable terminal 400 using a portable telephone mail service 600. When the user inputs the P-code attached to information
20 of interest from the P service terminal 100, he/she can obtain the print of information corresponding to the P-code. The portable terminal 400 of this embodiment can extract a P-code described in mail information, hold it in an internal memory, and input the held P-code to the
25 P service terminal 100 by infrared communication or the like.

A service such as a mail service becomes available when personal registration is done in the P service server 200. This registration can be done from, e.g., a terminal of a user (user terminal 700) through a Web.

5 Instead, the user may fill a registration form with predetermined items, and the operator of the P service server may perform registration processing in accordance with the described contents.

10 In this embodiment, two kinds of information are provided by the IP server 300 and registered/managed by the P service server 200. One is information (to be referred to as IP information hereinafter) provided to a user with or without charge on the basis of P-code designation by the user from the P service terminal 100
15 or the like. The other is information (to be referred to as advertisement information hereinafter) automatically selected by the P service server and attached to information (e.g., IP information) acquired in accordance with P-code input by the user.

20 As examples of services realized in the above-described P service system, the following services will be mainly described in this embodiment. (1) User registration: a personal P-code is given in accordance with registration application from the user terminal 700
25 to the P service server. (2) IP information registration: in accordance with IP information

registration application from the IP server 300, IP information is registered in the P service server 200, and a P-code for the IP is given. (3) Advertisement information registration: in accordance with an advertisement information registration application, advertisement information is registered in the P service server 200. (4) Information service: by inputting the P-code (P-code for the IP) of desired information from the P service terminal 100, a print output of the desired information is obtained. (5) Mail service: by inputting the user's P-code (personal P-code) from the P service terminal 100, mail addressed to the user is printed. (6) Personal information service: by inputting the user's P-code from the P service terminal 100, a print output of information set/registered for the user in advance is obtained. (7) Distribution service: desired information is uploaded from the P service terminal 100 to the P service server 200 in advance and printed from the P service terminal 100 as needed.

Each of these services will be described later in detail. The services and functions realized by the P service system of this embodiment are not limited to the above-described services and functions.

<Arrangement of P Service Terminal>

Fig. 2 is a view showing the schematic appearance of the P service terminal 100 of this embodiment.

Referring to Fig. 2, a printer 101 forms a visible color image by, e.g., a laser beam scheme. A scanner 102 optically reads an original image and converts it into digital image data. The printing scheme of the printer 101 is not limited to the laser beam scheme, and any other scheme such as a thermal transfer scheme or ink-jet printing scheme can be used. Using the printer 101 and scanner 102, the service terminal 100 can also be made to function as a copying machine. A main unit 103 controls communication with the P service server 200 or communication with the portable terminal 400 and performs various operation inputs and display corresponding to various operations.

In the main unit 103, a touch panel 104 receives an operation input by a user and presents various information to the user. An infrared communication section 105 is used to receive a P-code from a portable terminal having an infrared communication function by infrared communication. When a portable terminal is connected to a portable terminal connector 106, data (P-code) stored in the memory of the portable terminal is read out by the P service terminal 100. When a P-code is provided in a form of a bar code, a bar code reader 107 is used to read the bar code to acquire the P-code.

A disk unit 108 reads/writes data from/in a medium such as a floppy disk or MO. A settlement unit 110

performs settlement for the above-described various services. As a settlement method, various methods including settlement using cash or a credit card are available.

5 Fig. 3 is a block diagram showing the control arrangement of the P service terminal 100. The same reference numerals as in Fig. 2 denote the same parts in Fig. 3. A communication section 124 is connected to the P service server 200 through, e.g., a telephone line to
10 perform communication.

 A control section 120 controls each construction described with reference to Fig. 2. In the control section 120, a CPU 121 realizes various control operations in the P service terminal 100 in accordance
15 with control programs stored in a memory 122. User I/F control 122a controls execution of each of the following programs in accordance with a user's operation instruction input through the touch panel 104.

 Information service processing 122b, mail service
20 processing 122c, personal information service processing 122d, and distribution service processing 122e realize the above-described various services, i.e., information service, mail service, personal information service, and distribution service, respectively. Settlement
25 processing 122f realizes settlement processing using the settlement unit 110.

<Arrangement of Portable Terminal>

Fig. 4 is a view showing the schematic appearance of the portable terminal 400 capable of transmitting a P-code to the P service terminal 100. Like a general portable telephone, the portable terminal 400 has a liquid crystal display 410 and dial buttons and functions as a portable telephone. The portable terminal 400 can receive mail and displays its contents on the liquid crystal display 410. The cursor in the liquid crystal display can be moved using a left cursor 401 and right cursor 402 and can select a desired block in mail in cooperation with a block designation key 404. When a P-code key 403 is pressed while a certain block in mail is kept selected, data in the selected block is stored in the internal memory as a P-code. Instead, the P-code may be automatically searched for, extracted, and stored in the memory by pressing the P-code key 403 in a mail displayed state. Details of these operations will be described later with reference to Figs. 108 to 111.

An infrared communication section 405 outputs a P-code stored in the internal memory by infrared rays. The infrared rays output from the infrared communication section 405 are received by the infrared communication section 105 of the P service terminal 100 and recognized as a P-code. The portable terminal 400 also has a communication connector on its ^{bottom}~~button~~ surface so as to

exchange telephone number information between the terminal and a personal computer.

Fig. 5 is a block diagram for explaining the control arrangement of the portable terminal 400.

5 Referring to Fig. 5, a telephone function section 423 has functions necessary for communication processing as a portable telephone, including a loudspeaker, microphone, and radio communication functions. A communication connector 424 is generally used to connect
10 the portable terminal to a personal computer and upload or download a telephone number or the like. In this embodiment, when the communication connector 424 is connected to the portable terminal connector 106 of the P service terminal 100, a P-code can be transferred to
15 the P service terminal 100. A button group 425 corresponds to the group of various operation buttons described with reference to Fig. 4 (including the dial button group).

A control section 420 realizes control of the
20 constructions described with reference to Fig. 4 or various control operations in the portable terminal 400 in accordance with control programs stored in a memory 422. Of the programs stored in the memory 422, portable terminal control 422a is a program unit for realizing a
25 function as a normal portable telephone. P-code extraction processing 422b is a program unit for

A

the process
~~A processing~~ of extracting a P-code from received mail and
storing the P-code in a P-code storage area 422c. As
described above, to extract a P-code, data in a manually
selected block is extracted as a P-code, or a P-code is
5 automatically identified and extracted from mail data.
P-code transmission processing 422d is a program unit
for transmitting a P-code stored in the P-code storage
area 422c to the P service terminal through the infrared
communication section 405 or communication connector 424.
10 <Arrangement of P Service Server>
The P service server 200 will be described next.
Fig. 6 is a block diagram showing the schematic
arrangement of the P service server 200. A control
section 201 has a CPU 202 and memory 203. The CPU 202
15 realizes various services in the P service server 200 in
accordance with control programs stored in the memory
203. The memory 203 stores the control programs to be
executed by the CPU 202. Information registration
processing 203a is a program module for registering,
20 e.g., IP information, advertisement information, user
information (personal information), the distribution
data. P-code issue processing 203b is a program module
for assigning a P-code for specifying each registered
information. Service processing 203c acquires IP
25 information, advertisement information, mail data, or
distribution data or registers distribution data in

accordance with a P-code transmitted from the P service terminal 100. Advertisement search processing 203d searches for advertisement information to be attached to a print output in the P service terminal. By attaching
5 advertisement information, the information output charge is canceled by advertisement charges to reduce the cost for the user to bear in outputting information (printing). Data output processing 203e attaches advertisement information obtained by advertisement
10 search processing to information obtained on the basis of a P-code input from the P service terminal 100, lays out the pieces of information on a printing paper sheet, and generates and outputs print data.

A communication section 204 is connected to the P
15 service terminal through a line or to each IP server 300 through a Web.

A P-code database 205 stores a table group 205a associated with P-codes and entity 205b of contents. The table group 205a includes an IP information registration
20 table (Fig. 7), advertisement information table (Fig. 8), user information table (Fig. 9), mail service P-code table (Fig. 10), distribution service P-code table (Fig. 11), personal information service P-code table (Fig. 12), personal information table (Fig. 13), owner
25 information table (Fig. 14), and terminal information table (Fig. 15).

includes the path and file name of an entity file.

In the P service system of this embodiment, the IP server 300 can issue a P-code within an allowable range. Hence, IP information is registered by the P service
5 server 200 or IP server 300. A server which has registered IP information holds the contents and IP information registration table. That is, the entity of IP information and IP information registration table are present in the P service server 200 or IP server 300.

10 Fig. 8 is a view showing a data structure example of the advertisement information table. The advertisement information table is generated and recorded when an advertiser registers advertisement information. The advertisement properties, link, and
15 entity file information of the advertisement information are stored in correspondence with an assigned P-code. The advertisement properties store information representing the owner of the advertisement information and insertion conditions of the advertisement
20 information. The "link information to IP information" of the advertisement properties stores a target keyword list and target keyword weight list used in the advertisement search processing 203d.

The "link" stores the P-code of advertisement
25 information to be linked. In the "entity file information", the path name and file name for specifying

the file of the advertisement information are registered.
The entity of the advertisement information can be
present in either the P service server or IP service
server. However, the advertisement information table is
5 always stored in the P-code database 205 of the P
service server 200. When the entity of advertisement
information is present in the IP service server,
information for specifying the IP service server is
included in the entity file information of the
10 advertisement information table (in this embodiment, the
IP server is specified by the P-code, and this will be
described later).

Fig. 9 is a view showing a data structure example
of a user information table. The user information table
15 is generated and recorded when the user registers
himself/herself as a member of the P service system and
includes a user profile, personal information, mail
service information, distribution service information,
and personal information service information. In the
A 20 user ^{profile is}~~profile~~ information representing the address and
objects of interest of the user. The "personal
information table" in the user profile stores pointers
to the personal information table in which the personal
secret matters including the address, name, telephone
25 number, and credit card number of the user are
registered, as shown in Fig. 13. In the mail service

information, distribution service information, and
personal information service information, information
necessary for the mail print service, distribution
service, and personal information service are registered,
5 respectively.

Fig. 10 is a view showing a data structure example
of a P-code table for the mail service. As shown in
Fig. 10, in correspondence with the P-code for the mail
service, a "mail properties" representing the subject
10 (title) and sender of mail and entity file information
representing the file of mail data are registered.
Referring to Fig. 10, the P-code has a parent code
section "telephone number" and attached section (suffix
(also to be spelled as "surfix")) "# number". The
15 subcode herein means the "number" section in the
attached section.

Fig. 11 is a view showing a data structure example
of a P-code table for the distribution service. As shown
in Fig. 11, in correspondence with the P-code for the
20 distribution service, the "distribution information
properties" representing the title, valid dates of the
distribution information, and the password given to the
distribution information, and entity file information
representing the distribution information file are
25 registered. Referring to Fig. 11, the P-code has a
parent code section "telephone number" and attached

section (surfix) "- number". The subcode herein means the "number" section in the attached section.

Fig. 12 is a view showing a data structure example of a P-code table for the personal information service.

5 As shown in Fig. 12, in correspondence with the P-code
for the personal information service, the "personal
information properties" representing the title and final
print date and "registered P-code information"
representing the list of registered P-codes are
10 registered. The P-code list is a P-code group which is
set and registered by the user in advance. Referring to
Fig. 12, the P-code has a parent code section "telephone
number" and attached section (surfix) "## number". The
subcode herein means the "number" section in the
15 attached section.

Fig. 13 is a view showing a data structure example of a personal information table. The personal information table is contained in the user information table, as described above with reference to Fig. 9.

Fig. 14 is a view showing a data structure example of an owner information table. This table is linked to the IP information registration table shown in Fig. 7, ^{and is the} ~~is~~ "owner ID" in the advertisement information table shown in Fig. 8. As shown in Fig. 14, information associated with the owner (information provider or advertiser) is registered.

Fig. 15 is a view showing a data structure example of a terminal information table. The terminal information table is held for each P service terminal.

<Arrangement of IP Server>

5 Fig. 16 is a block diagram showing the typical arrangement of the IP server 300. Referring to Fig. 16, a control section 301 has a CPU 302 and memory 303 and executes various processing operations in the IP server 300. A display 304 displays various data under the

10 control of the control section 301. An input section 305 comprises a pointing device such as a keyboard or mouse. A data storage section 306 stores the "entity of IP information" registered in the P service system and "IP information registration table" associated with the IP

15 information (the IP information registration table is the same as that shown in Fig. 7). A communication section 307 is connected to the P service server 200 through a line or the like.

 The IP server 300 acquires an available P-code

20 value from the P service server 200 and issues a P-code when IP information is registered from the user terminal. At this time, the entity of IP information and the IP information registration table are held by the data storage section 306. When an information request from

25 the P service server 200 is received, the entity (contents) of the IP information is extracted in

A

accordance with the designated P-code and ^{is transmitted} ~~transmits it~~ to the P service server 200.

<P-Code>

The P-code used to specify information or the like
5 in this embodiment will be described next.

Fig. 17 is a view for explaining the data
structure of the P-code used in the P service system
according to this embodiment. As shown in Fig. 17, the
P-code can be divided into three sections: a
10 "classification section", "number section", and
"attached section".

The classification section is a 16-bit code
containing a P-code type bit representing that the input
P-code number is an IP P-code (information P-Code) or
15 personal P-code (personal user P-Code), version
information, and country number. When a P-code number is
input to the P service terminal 100, the contents of
this classification section are automatically attached
by the terminal.

20 First, it is determined whether the input P-code
is a personal P-code or IP P-code to set the P-code type
bit. In this embodiment, a telephone number is used as
the number section of the personal P-code. If the number
input to the P service terminal 100 has 11 consecutive
25 digits or less, it is determined that a telephone number
is input, i.e., a personal P-code is input, and the

P-code type bit is set at "1". On the other hand, if a number sequence hyphenated in units of four digits (in units of four numbers) is input as a P-code number, it is identified that a nontelephone number is input, and
5 the P-code type bit is set at "0". Subsequently, version information is set, and a country number representing the country where the P service terminal is installed is set (when a country is designated from the P service terminal, the number of the designated country is set).

10 The number section has a number (to be referred to as a P-code number hereinafter) directly input by the user. This is a number inserted to a newspaper, magazine, or homepage by the information provider. Note that a telephone number is used as a personal P-code number.

15 When the above-described P-code type bit is 1, i.e., a personal P-code, 40 bits are allocated to the number section, as shown in Fig. 17, in which a numerical value represented by the telephone number is input. The remaining eight bits are used as an attached
20 section.

On the other hand, when the flag bit is 0, i.e., an IP P-code, 39 bits are allocated to the number section, as shown in Fig. 17, and the remaining nine bits are used as an attached section. Of the 39 bits of
25 the number section, the first bit represents a P service server identification bit (1 bit), and the subsequent

0011100 041100 0547397 06E24560

three bits represent a class category. Since the P service server identification bit is 0 for a site except the P service server, only three bits representing a class category are contained in the first four bits, and
5 the first digit of the P-code number represents a class category (numerical values 1 to 5). The class category has the same meaning as that of an IP address. As shown in Fig. 17, numerical values 1 to 5 indicated by the three bits represent five classes from minimum to
10 maximum scales. For example, for class 1 (minimum scale), 24 bits are used as a site identification number (to also be referred to as an external code hereinafter), and the remaining 11 bits construct an ID code (to also be referred to as an internal code hereinafter) freely
15 usable in the site. When the class category is determined in accordance with the scale of an IP server, the number of P-codes assigned to the IP server is determined depending on the scale of the IP server.

The attached section indicates the identification
20 number of a subcategory of the contents identified by the above classification section + number section. For an information P-code, for example, "^{professional}~~professional~~
A baseball game result" has categories "result of today",
A "result of ^{yesterday}~~yesterday~~", "result of day before
25 yesterday", ..., and "tip on horse racing" has categories "site" and "race". For a personal P-code, the attached

section is used for a mail box number or personal information number.

Especially, in this embodiment, a plurality of types of "attached sections" can be connected to one number section as suffixes. When grouping is designated for P-codes, the P-code can be linked to other IP information in units of suffixes. When the code of the number section is input as a P-code, information having the maximum surfix value is selected and presented as IP information. This can cope with information such as "results of professional baseball games of yesterday", which requires frequent update and addition of information". Assume that a new result of professional baseball game is generated. Next day, the game result of yesterday is grouped in correspondence with a P-code with an incremented surfix, thereby linking the P-code with the incremented surfix to the IP information of the game result. Hence, when a P-code number is designated to obtain the "result of professional baseball game of yesterday", information having the maximum surfix attached to the P-code number is extracted and presented to the user.

When a P-code has an attached section, it may be directly input by the user. However, instead of directly inputting the number, the P-code with an attached section can be input by selecting it from a menu. More

specifically, when the user inputs only the P-code number of a P-code having an attached section, the value of the corresponding P-code (number section + attached section) and its properties (title and the like) are transmitted from the P service server to the P service terminal 100. The P service terminal 100 displays a selection list using the information on the touch panel 104 as a menu. When the user selects a desired content from the selection list, a corresponding P-code (number section + attached section) is transmitted to the P service server, and the selected content is sent to the P service terminal. In this embodiment, an example will be described, in which a personal P-code uses, as a number section, a numerical value input by the user as a "telephone number", and as an attached section, a code formed from a sequence of a "predetermined symbol" and "subcode", and "#", "-", or "##" is used as the "predetermined symbol". In this case, when the personal P-code is input, the "predetermined symbol" registered in advance is detected from the P-code, and a service predetermined in accordance with the type of the detected "predetermined symbol" is executed (a mail service for "#", distribution service for "-", and personal information service for "##").

Fig. 18 shows the structure of the above P-code. When a P-code is stored in the memory of a

portable terminal, all constituent elements ("classification section", "number section", and "attached section") of the P-code are registered in the memory and input to the P service terminal. This enables omission of an operation such as menu selection, so load of the user can be reduced.

<Outline of Operation of System>

The outline of processing by the P service server of this embodiment will be described next with reference to Figs. 19 and 20.

In steps S101 to S109, processing to be executed is selected on the basis of IP information, command, and P-code input from the P service terminal 100, IP server 300, or user terminal 700. For example, when input data is a user registration request, the flow advances from step S102 to step S111 to issue a personal P-code and perform user registration processing by the information registration processing 203a and P-code issue processing 203b. By this user registration processing, the user information table shown in Fig. 9 and personal information table shown in Fig. 13 are generated and registered. When an IP information registration request is input, the flow advances from step S103 to step S112 to issue an IP P-code from P-codes assigned to the IP server which is requested to register the IP information. In step S113, IP information registration processing is

performed. By this IP information registration processing, the IP information registration table shown in Fig. 7 is generated and registered. When an advertisement information registration request is input, the flow advances from step S104 to step S114 to issue a P-code. In step S115, advertisement information registration processing is executed. By this advertisement information registration processing, the advertisement information table as shown in Fig. 8 is generated and registered in the P service server 200.

When a P-code is input from the P service terminal 100, processing requested by the P-code is determined from processing operations in steps S105 to S109. When the P-code is an IP P-code (the P-code type bit is 0), it is determined that the information service is requested. The flow advances from step S105 to step S116 to acquire the entity and properties of IP information from the P-code and generate preview data. When the P-code is a personal P-code (the P-code type bit is 1) and is registered in the mail service information of the user information table, it is requested that the mail service is requested, and the flow advances from step S106 to step S117. In step S117, the entity and properties of mail data are acquired from the mail P-code table on the basis of the P-code.

When the input P-code is a personal P-code and is

registered in the personal information service
information of the user information table (Fig. 9), it
is determined that the personal information service is
requested, and the flow advances from step S107 to step
5 S118. In step S118, the list of IP P-codes is acquired
by looking up the personal information service P-code
table (Fig. 12), and IP information and their properties
of all P-codes registered in this list are acquired.

When the input P-code is a personal P-code and is
10 registered in the distribution service information of
the user information table, it is determined that data
extraction in the distribution service is requested, and
the flow advances from step S108 to step S119. In step
S119, a password registered in correspondence with the
15 data is requested. It is determined by looking up the
distribution service P-code table whether an authentic
password is received, and the entity and properties of
distribution data corresponding to the P-code are
acquired.

20 When it is determined that distribution data
registration in the distribution service is requested,
the flow advances from step S109 to step S123 to execute
distribution data registration processing including
P-code issue processing and processing of registering a
25 password corresponding to the data and notify the user
of the data registration and assigned P-code. In this

described by exemplifying a case wherein user registration is done from the user terminal 700 of the user through the Web.

When the user accesses user registration of the P
5 service server 200 from the user terminal 700, the P
service server 200 executes user registration processing
in step S111.

Fig. 21 is a flow chart of user registration processing.

10 In this user registration processing, the P
service server 200 displays various windows for user
registration on the display of the user terminal 700 and
causes the user to sequentially input matters to be
registered by so-called GUI.

15 In step S1000, the P service server 200 determines
whether the user has selected new user registration or a
change in user registration that has been already
performed. For the former processing, the flow advances
to step S1001. For the latter processing, the flow
20 advances to step S1005.

In step S1001, new registration processing is performed. In this new registration processing, a dialog box shown in Fig. 22 is displayed first on the display of the user terminal 700.

```
25      This dialog box has a "name/address" button 1000,
      "password" button 1010, "place of employment" button
```

1020, "credit card" button 1030, "service" button 1040, "personal information" button 1050, "personal information 2" button 1060, "desired information" button 1070, "printing paper" button 1080, and "favorite information registration" button 1090. The user can register matters corresponding to the respective items by clicking the buttons.

When the "name/address" button 1000 is clicked in the dialog box shown in Fig. 22, a dialog box shown in Fig. 23 is displayed. The user must input, from the user terminal 700, at least the name, address, and one of the telephone number and portable telephone number as indispensable input matters. At the end of the input, the "OK" button is clicked, the input contents are stored, and the dialog box shown in Fig. 22 is displayed again. When the "cancel" button is clicked, the dialog box shown in Fig. 22 is displayed again without storing the input contents. This also applies to processing to be described below.

When the "password" button 1010 is clicked in the dialog box shown in Fig. 22, a dialog box shown in Fig. 24 is displayed. The user inputs a desired password to the "password" column. The password is registered to prevent a third party from using the P service system under disguised ownership. Hence, the password is an indispensable input matter in principle.

Since the input password is displayed by "*", the user is caused to input the password again to the "password (confirmation)" column to prevent any input error.

5 When the "place of employment" button 1020 is
clicked in the dialog box shown in Fig. 22, a dialog box
shown in Fig. 25 is displayed. The user can arbitrarily
input matters associated with the place of employment.

When the "credit card" button 1030 is clicked in the dialog box shown in Fig. 22, a dialog box shown in Fig. 26 is displayed. When the user will pay a charge for the P service system using a credit card, he/she designates a credit card of his/her own in this dialog box. If no credit card is designated, it is regarded that the user will pay in cash.

When the "service" button 1040 is clicked in the dialog box shown in Fig. 22, a dialog box shown in Fig. 27 is displayed. From the mail service, personal information service, and distribution service provided by the P service system, the user selects services desired based on the P-code assigned by this user registration, and checks check boxes corresponding to the services. A service without a check mark is not available on the basis of the P-code assigned by this user registration.

When the "personal information" button 1050 is

search for free IP information associated with the checked items, attach the information to the margin portion, and output it. The checked items can also be used for advertisement information search processing.

5 When the "printing paper" button 1080 is clicked in the dialog box shown in Fig. 22, a dialog box shown in Fig. 31 is displayed. In receiving a print output from the P service terminal 100, the user can designate the output format. For example, when the "visibility
10 priority" button in the dialog box shown in Fig. 31 is checked, priority is given to the layout of the print, and information obtained by the P service system is printed in a layout easy to see. When the "page count
15 priority" check button is checked, priority is given to saving of page count, so the print cost is expected to
A be saved. When ^{the} "details" button is clicked, desired conditions can be selected and designated from a plurality of layout patterns, the amount of advertisement information, and font sizes, which are
20 registered on the P service system.

 When the "favorite information registration" button 1090 is clicked in the dialog box shown in Fig. 22, IP information to be subjected to the personal information service can be set. This setting is done by
25 listing IP P-codes corresponding to an IP information group desired by the user. A plurality of pieces of

favorite information can be registered. The dialog box displayed at this time is the same as that for registration of a frame of the personal information service for a later description of various services and
5 therefore is not illustrated.

When the user clicks the "OK" button in the dialog box shown in Fig. 22, the P service server 200 determines that all inputs are complete. The flow advances to step S1002 to check whether all the
10 above-described indispensable input matters are input. If YES in step S1002, the flow advances to step S1003. If NO in step S1002, a predetermined alarming message is displayed, and the flow returns to step S1001. When the user clicks the "cancel" button, processing is ended
15 without registration.

In step S1003, the P service server 200 issues the personal P-code. Especially, one of the portable telephone number and telephone number input by the user in the dialog box shown in Fig. 23 is attached as a
20 "number section", and then, the P-code is sent to the user terminal 700, thereby giving the P-code to the user. This issue processing will be described later in detail with reference to Fig. 70.

In step S1004, the information input by the above
25 processing is stored in the user information table shown in Fig. 9 in correspondence with the new personal P-code

given to the user in this user registration. After that, user registration processing is ended.

When a change in user registration already performed is selected in step S1000, the flow advances
5 to step S1005.

In step S1005, registration change processing is performed. In this registration change processing, a dialog box shown in Fig. 32 is displayed on the display of the user terminal 700 first. The dialog box shown in
10 Fig. 32 has the same structure as that of the dialog box shown in Fig. 22. Referring to Fig. 32, buttons corresponding to the buttons 1000 to 1090 of the dialog box shown in Fig. 22 are indicated by adding "'" to the same reference numerals as in Fig. 22.

15 When the user clicks the buttons 1000' to 1090', dialog boxes as shown in Figs. 23 to 31 are displayed in correspondence with the buttons. In the displayed dialog box, matters input in the past user registration are displayed together.

20 The user can change the displayed contents while looking at them. For example, when the "password" button 1010' in Fig. 32 is clicked, a dialog box shown in Fig. 33 is displayed. The user can input a new password to the "password" column to change the password. For
25 confirmation, the new password is input to the "password (confirmation)" column again. After the input, the "OK"

button is clicked to store the changed contents.

When the user clicks the "OK" button in the dialog box shown in Fig. 32, the P service server 200 determines that all changes are made, and the flow advances to step S1006 to check for confirmation whether the above-described indispensable input matters are erased by errors upon the change. If all the indispensable input matters have been input, the flow advances to step S1004. If matters are erased, a predetermined alarming message is displayed, and the flow returns to step S1005.

In step S1004, the P service server 200 updates the corresponding matters in the user information table in accordance with the changed contents.

All user registration processing operations are complete. In the above new registration processing, input items are sequentially selected from the menu shown in Fig. 22, and necessary matters are input. However, a so-called "wizard" form may be used to automatically sequentially display the input windows and cause the user to input necessary matters. However, to change the registered contents, the menu for selecting a desired matter as shown in Fig. 32 is preferable.

<IP Information Registration>

The information provider who provides IP information in the P service system must register

contents of the IP information and the like in the P
service server 200 or IP server 300.

To do this registration, the information provider
accesses the P service server 200 or IP server 300 from
5 a terminal (not shown) (to be referred to as an
information provider terminal hereinafter) of the
information provider through the Web or presents a
storage medium such as a CD-ROM in which contents of IP
information and the like are stored to the operator of
10 the P service system.

The procedure of IP information registration will
be described below by exemplifying a case wherein the
information provider registers IP information in the P
service server 200 through the Web.

15 When the information provider accesses IP
information registration in the P service server 200
from the information provider terminal, the P service
server 200 executes processing in step S112 in Fig. 19
and internally issues an IP P-code for the information
20 provider. After that, the flow advances to step S113 to
execute IP information registration processing.

Fig. 34 is a flow chart of IP information
registration processing.

In this IP information registration processing,
25 the P service server 200 displays windows for IP
information registration on the display of the

information provider terminal and causes the information provider to sequentially input matters to be registered by so-called GUI, as in the above-described user registration processing.

- 5 In step S1010, a dialog box shown in Fig. 35 is displayed. It is determined whether the information provider is a member of the P service system. A member means a person who has made an application to the P service system in advance as an information provider. A
- 10 nonmember cannot provide pay IP information. A membership number and password are assigned in accordance with an application.

- When the information provider is a member, he/she checks the radio button "Yes" in this dialog box and
- 15 also inputs the membership number. When the information provider is a nonmember, he/she checks the radio button "No". When "next" is clicked, the flow advances to step S1011 for a nonmember. For a member, a dialog box shown in Fig. 36 is displayed to request to input a password.
- 20 If the password input by the information provider is authentic, the flow advances to step S1012.

- When "next" is clicked in each dialog box, input information is stored, and the flow advances to the next processing. When "back" is clicked, input information is
- 25 stored, and the flow returns to immediately preceding processing. When "cancel" is clicked, the flow returns

A entity(contents) of IP information stored in the information provider terminal. In this case, a plurality of file names can be designated. The IP information to be registered may be either character information or an
5 image.

When the "designate file" button is clicked, a dialog box in Fig. 41 that shows the list of IP information files stored in the information provider terminal can be displayed. In this case, the information
10 provider can easily select an IP information file. To cancel a file selected once, the file is designated in the dialog box shown in Fig. 40, and the "delete" button is clicked. When "next" is selected in the dialog box shown in Fig. 40, the flow advances to step S1015.

15 In step S1015, the contents of the file designated in step S1014 are displayed as a preview (Fig. 42), and the information provider is made to confirm it. After the confirmation, when the information provider clicks the "transfer to server" button, a dialog box shown in
20 Fig. 43 is displayed, and the designated file is transferred to the P service server 200. After the transfer, the flow advances to step S1016.

In step S1016, a property of the transferred IP information is set. In setting the property, a dialog
25 box shown in Fig. 44 is displayed, so the date of start of insertion and valid dates of the IP information can

001140" 46544560

be set. In this setting, the valid dates of the IP
P-code and those of the IP information can be
independently set. The valid dates of the P-code may be
automatically set by adding a predetermined period to
5 the valid dates of the IP information, as will be
described later with reference to Fig. 73. When "next"
is clicked in the dialog box shown in Fig. 44, a dialog
box shown in Fig. 45 is displayed to set another
property.

10 In this dialog box, whether a change in size of
registered IP information is allowed when it is output
from the P service terminal 100 is set.

This setting is required because size reduction
may be required on the P service terminal 100 side due
15 to the paper of the P service terminal 100 or layout of
a plurality of IP information output to one paper sheet.
If the size can be freely changed on the P service
terminal 100 side, the printed contents may be unclear
depending on the contents of the IP information. Hence,
20 the information provider is allowed to set the allowable
range of the font size or magnification. When "next" is
selected in the dialog box shown in Fig. 45, a dialog
box shown in Fig. 46 is displayed to set still another
property.

25 In this dialog box, whether the information
provider permits automatic attachment of advertisement

information when the IP information registered is output from the P service terminal 100 is set. The information provider checks one of the radio buttons "permit", "permit for lower surface", "not permit" to select setting. Advertisement information is attached within the selected range. When "next" is selected in the dialog box shown in Fig. 46, a dialog box shown in Fig. 47 is displayed to set still another property.

In this dialog box, a password can be set to allow only a specific user to use the registered IP information. To set a password, the check box "set password" is checked, and a desired password is input to the "password" column. After input, when "next" is clicked, a dialog box shown in Fig. 48 is displayed. Re-input is requested to prevent a password input error. When the "register" button is clicked, the password is stored. When password setting is unnecessary, "next" is clicked without any processing in the dialog box shown in Fig. 47. In either case, a dialog box shown in Fig. 49 is displayed to set still another property.

In this dialog box, the genre and keywords of IP information to be registered are input such that they can be used for advertisement search processing. The items to be input are "genre", "subgenre", and "keyword".

25 "Genre" and "subgenre" are listed in drop-down list boxes. For example, when the right arrow of the "genre"

column is clicked, the list of items of the "genre" column is displayed, as in a dialog box shown in Fig. 50. The information provider can select from this list a category most suitable to the IP information to be registered. In addition, keywords associated with the concrete contents of the IP information registered can be arbitrarily selected and input to the "keyword" column. An input keyword can be set by the "add" button, and the set keyword can be canceled by the "delete" button.

When the check box "negative link to advertisement" is checked, selection of advertisement information inappropriate to the contents of the registered IP information can be avoided.

Instead of or together with setting the property in the dialog box shown in Fig. 49, a property in a dialog box shown in Fig. 51 can be set.

In the dialog box shown in Fig. 51, the title and summary of the registered IP information are input. This summary is used for advertisement search processing. In addition, when the IP information is requested in the information service, the summary is temporarily disclosed to the user instead of immediately providing the entity of the IP information to the user, thereby increasing the width of IP information selection by the user or reducing the charge.

Property setting in step S1016 is ended, and the flow advances to step S1017.

In step S1017, a dialog box shown in Fig. 52A is displayed to select whether the registered IP
5 information is to be subjected to group setting. With group setting, pieces of IP information are associated with each other. This processing is used to handle information having the same object whose contents are updated over time, including the results of professional
10 baseball games and stock information.

If group setting is not desired, the information provider clicks the "cancel" button, and in this case, the flow advances to step S1019.

If group setting is desired, whether the
15 registered IP information is to be added to an existing group or a new group is selected by a radio button in the dialog box shown in Fig. 52A.

To add the IP information to an existing group, the IP P-code of the link destination is input. The
20 P-code displayed in the "P-code to be registered" column is the P-code assigned to the IP information to be registered this time.

When a new group is selected, and the "OK" button is clicked, a dialog box shown in Fig. 52B is displayed.
25 The title, contents, and update schedule of the group are input. The input data are finally stored in the

Information
A Frame ~~information~~ storage area of the IP information registration table (Fig. 7).

In either case, when the "OK" button is clicked, a dialog box shown in Fig. 52C is displayed, and registration matters for group setting are displayed. This display is done when the IP information to be registered this time is added to an existing group. "Link number #77" in this display means that the IP information registered this time is also used as a P-code in which an attached section (surfix) "#77" is attached to the IP P-code (parent code section) of the link destination. That is, the IP information subjected to group setting can be accessed as the IP P-code of itself or as the IP P-code of the link destination (identified by the attached section), and the latter is mainly used to update information. When the "OK" button is clicked, the flow advances to step S1019.

In step S1019, a dialog box shown in Fig. 53 is displayed. The list of input matters is displayed together with the IP P-code assigned to the registered IP information. When the information provider confirms display and clicks the "register" button, the flow advances to step S1020.

In step S1020, the P service server 200 stores the information input by the above processing in the IP information registration table shown in Fig. 7 in

correspondence with the IP P-code assigned to the information provider. The information can also be transferred to the IP server 300 and held by the IP server 300.

5 When the information provider will register IP information not in the P service server 200 but in the IP server 300 from the information provider terminal, registration is generally done according to the above-described procedure.

10 In this case, the P service server 200 allocates a usable IP P-code area to the IP server 300 in advance. The IP server 300 can assign an IP P-code to the information provider from the IP P-codes in the allocated area. The IP server 300 notifies the P service
15 server 200 of at least the assigned P-code to perform IP information registration processing. This will be described later with reference to Figs. 71 to 74.

 In this way, the entire IP information registration processing is ended.

20 <Advertisement Information Registration>

 In the P service system, an advertisement provider who provides advertisement information must register the contents of advertisement information in the P service server 200 or IP server 300.

25 To do this registration, the advertisement provider accesses the P service server 200 or IP server

300 from a terminal (not shown) (to be referred to as an advertisement provider terminal hereinafter) of the advertisement provider through the Web or presents a storage medium such as a CD-ROM in which contents of advertisement information are stored to the operator of the P service system.

The procedure of advertisement information registration will be described below by exemplifying a case wherein the advertisement provider registers advertisement information in the P service server 200 through the Web.

When the advertisement provider accesses advertisement information registration in the P service server 200 from the advertisement provider terminal, the P service server 200 executes processing in step S114 in Fig. 19 and internally issues a P-code for advertisement information. This P-code is exclusively used for internal processing of the P service server 200 and therefore is not disclosed to the advertisement provider in principle.

After that, the flow advances to step S115 to execute advertisement information registration processing.

Fig. 54 is a flow chart of advertisement information registration processing.

In this advertisement information registration

001140 041100 09547397

processing, windows for advertisement information registration are displayed on the display of the advertisement provider terminal, and the advertisement provider is caused to input matters to be registered by
5 so-called GUI, as in the above-described user registration processing and IP information registration processing.

In step S1050, a dialog box shown in Fig. 55 is displayed, and it is determined whether the
10 advertisement provider is a member of the P service system. A member means a person who has made an application as an information provider in advance. A nonmember cannot provide advertisement information because advertisement insertion is charged for. A
15 membership number and password are assigned in accordance with an application.

When the advertisement provider is a member, he/she checks the radio button "Yes" in this dialog box and also inputs the membership number. When the
20 advertisement provider is a nonmember, he/she checks the radio button "No". When "next" is clicked, the flow advances to step S1051 for a nonmember. For a member, a dialog box shown in Fig. 56 is displayed to request to input a password. If the password input by the
25 advertisement provider is authentic, the flow advances to step S1052.

When "next" is clicked in each dialog box, input information is stored, and the flow advances to the next processing. When "back" is clicked, input information is stored, and the flow returns to immediately preceding processing. When "cancel" is clicked, the flow returns to the first dialog box without storing input information. This also applies to the following processing.

In step S1051, a dialog box shown in Fig. 57 is displayed to cause the advertisement provider as a nonmember to input information for specifying the advertisement provider. This is because advertisement insertion is charged for, as described above. After the input, when "next" is clicked, the flow advances to step S1052.

In step S1052, a dialog box shown in Fig. 58 is displayed to designate advertisement information to be registered. The advertisement provider inputs the file name of the entity (contents) of advertisement information stored in the advertisement provider terminal. In this case, a plurality of file names can be designated. The functions of the "designate file" and "delete" buttons are the same as in the above-described IP information registration processing shown in Fig. 40.

The advertisement information to be registered may be either an image or character information.

generation of a series of advertisement information.
When "next" is selected in the dialog box shown in
Fig. 66, a dialog box shown in Fig. 67 is displayed to
set still another property.

5 In this dialog box, a charge for insertion of the
advertisement information is set. In this dialog box, a
charge per insertion of advertisement information is
displayed, and the limit of the total charge can be
designated by setting the print count or the upper limit
10 of charge for insertion. When the radio box "designate
maximum print count" is checked, the count can also be
designated. When the radio box "designate upper limit of
advertisement charge " is checked, the upper limit of
charge for insertion can also be designated.

15 Property setting in step S1054 is ended, and the
flow advances to step S1055.

 In step S1055, a dialog box shown in Fig. 68 is
displayed. The list of input matters is displayed. The
P-code is not displayed in principle. When the
20 advertisement provider confirms the display and clicks
the "register" button, the flow advances to step S1056.
When the "register" button is clicked, a dialog box
shown in Fig. 69 may be displayed to allow the
advertisement provider terminal to print the particulars
25 of the registered advertisement information.

 In step S1056, the P service server 200 stores the

information input by the above processing in the advertisement information table shown in Fig. 8 in correspondence with the P-code issued in advance. The information may be transferred to the IP server 300. The
5 P service server 200 always holds the properties (advertisement information table) of the registered advertisement information. However, the entity (contents) itself can be held by either the P service server 200 or IP server 300.

10 When the advertisement provider will register advertisement information not in the P service server 200 but in the IP server 300 from the advertisement provider terminal, registration is generally done according to the above-described procedure.

15 In this case, the P service server 200 allocates a usable P-code area to the IP server 300 in advance. The IP server 300 can assign a P-code from the P-codes in the allocated area. The IP server 300 finally transfers the assigned P-code and its table information to the P
20 service server 200 to perform advertisement information registration processing.

In this way, the entire advertisement information registration processing is ended.

<P-code Issue Processing>

25 P-code issue processing in steps S111, S112, and S114 in Fig. 19 will be described next.

00110" 26E24560

Fig. 70 is a flow chart for explaining the personal P-code issue procedure in step S111.

When user information is registered, one of the portable telephone number, telephone number, and FAX number of the user is input by the above-described procedure according to GUI. For a personal P-code, one of the input numbers is used for the number section (P-code number) of the P-code. In this embodiment, priority is given in the order of the portable telephone number, telephone number, and FAX number. Hence, when a plurality of numbers are input by the user, the number used for the number section of the P-code is determined in accordance with this priority. For example, when a portable telephone number and telephone number are input, the portable telephone number with a higher priority is used to issue a P-code.

When the portable telephone number is input, the flow advances from step S3001 to step S3004 to extract the portable telephone number. If not the portable telephone number but the telephone number is input, the flow advances from step S3002 to step S3005 to extract the telephone number. If only the FAX number is input, the flow advances from step S3003 to step S3006 to extract the FAX number. If none of the portable telephone number, telephone number, and FAX number are input, the flow advances to error processing in step

S3009 to prompt the user to input at least one of the portable telephone number, telephone number, and FAX number.

When the number is extracted in one of steps S3004, S3005, and S3006, it is checked in step S3007 whether the extracted number is not common to a used personal P-code. If NO in step S3007, the flow advances to step S3009 to notify the user of it. When the extracted number is unique in the personal P-code, the flow advances from step S3007 to step S3008 to determine the extracted number as the number section of the P-code and assign the P-code to the user.

In this way, the personal P-code is determined on the basis of the portable telephone number, telephone number, or FAX number of the user.

IP P-code issue in step S112 in Fig. 19 will be described next. An IP P-code is issued by the P service server 200 or IP server 300.

To issue an IP P-code by the IP server 300, personal information ID number (internal code) is connected to a site number (external code) assigned to the IP server in advance to generate a P-code. More specifically, each IP server has a site number (external code, Fig. 18) assigned from the P service server 200. In accordance with an IP information registration request, the IP server 300 assigns an internal code and

links the external code to the internal code to obtain one P-code. The number of P-codes that can be assigned by the IP server equals the number of internal codes. Hence, processing of assigning an external code to the IP server will be described first, and IP P-code issue processing will be described then.

Fig. 71 is a flow chart for explaining a procedure in which the P service server assigns the external code of a P-code to the IP server.

10 In step S3021, when a P-code request is received from the IP server, the site scale is determined in step S3022 (the site scale is determined in accordance with a scale request from the IP server). When the site scale is determined, four bits from the 17th bit to the 20th
15 bit in Fig. 18 are determined (since the code is to be assigned to an external server, the 17th bit (server identification bit) is "0"). In step S3023, the code value of the external code section determined in accordance with the site scale determined in step S3022
20 is determined. For example, when the site scale is medium, the 21st to 36th bits are used as bits for the external code, as shown in Fig. 18, so a code value represented by 16 bits is determined. The code value determined herein is a code that has not been assigned
A 25 yet to another ^{site}~~side~~ at that time.

Fig. 72 is a view showing the data structure of a

P-code use registration table used in this embodiment.
This P-code user registration table is held by the P
service server 200. As shown in Fig. 72, external codes
already assigned to sites (IP servers) and the URLs of
5 the sites are registered in correspondence with each
other in units of site scales including the minimal
scale, small scale, medium scale, large scale, and
maximal scale. In step S3023, an unused external code is
detected by looking up the P-code use registration table
10 and determined as an external code to be assigned. As
information to be registered in correspondence with an
external code, information capable of specifying the
database which stores information in the IP server, i.e.,
database identification information (address) suffixes,
15 and a URL need not always be used. This is because
information to be provided in accordance with
designation of a P-code in the system is not always
present on the Web.

In step S3024, the site that has requested a
20 P-code is notified of the value determined in steps
S3022 and S3023 as an external code. Upon receiving the
site number (external code) from the P service server
200, the site that has requested a P-code can issue a
P-code corresponding to IP information using personal
25 information ID bits (internal code) according to the
site scale.

In step S3025, the P-code use registration table shown in Fig. 72 is updated. More specifically, in the external code determined in steps S3022 and ^{S3023}~~S3023~~ and the URL (database identification information) of the site that has requested a P-code are registered in the P-code use registration table shown in Fig. 72 in correspondence with each other. When an IP P-code is designated later from the P service terminal 100, the P service server 200 can know the site that is to be notified of the designated P-code to obtain information by looking up this P-code use registration table.

P-code issue processing in the server (P service server or IP server) which has received an IP information registration request will be described ^{next}~~net.~~. In the following processing example, a P-code is issued using a P-code use table in which the valid date of each P-code is registered.

Fig. 73 is a view showing the data structure of the P-code use table. Each IP server holds a P-code use table as shown in Fig. 73 and looks it up in issuing a P-code.

The number section of a P-code (for an IP server, a number obtained by linking an external code and internal code; for the P service server 200, a number represented by the 17th to 55th bits) and the valid dates of the code are registered in the P-code use table. As the

valid dates of the code, the same data as the "valid
dates of code" in the IP information registration table
shown in Fig. 7 is used. In registering IP information,
dates set by the information provider by GUI in Fig. 44
5 are registered as the valid dates of the code.

Alternatively, a date after a predetermined period from the valid dates of information set by the information provider in IP information registration, e.g., a date after three months is automatically set. With this setting, a nonuse period of the P-code is given, and contents to which the same P-code is assigned can be prevented from largely changing after a certain day. Since a common external code is used in one site, only the internal code may be recorded in the column "number section of P-code" of the P-code use table.

For a personal P-code in the P service server 200, the number section of the P-code is constructed by a 40-bit code section. For this reason, the code represented by 40 bits is registered in the column

20 "number section of P-code".

Fig. 74 is a flow chart for explaining IP-code issue processing. When an IP information registration request is received, and step S112 in Fig. 19 is executed, a P-code usable in the server is detected by looking up the above-described P-code use table in step S3041. In step S3042, one of the usable P-codes is

determined and assigned to the IP information. To assign a P-code by the IP server, the above-described P-code use table is searched to acquire an unused internal code. The internal code is linked to the external code of the IP server, class category code (code representing the site scale), and server identification bit (= 0) to determine a P-code to be issued and assigned to the information. To assign a P-code by the P service server 200, a 39-bit unused code is connected to the identification bit (17th bit = 1) to obtain a P-code, as shown in Fig. 18.

An unused P-code means a P-code whose "term of validity of code" has expired. To determine whether a P-code is unused, the table may be searched for a P-code that has expired at the time of issue. Alternatively, time information of year, month, and day may be always compared with the valid dates of code in the table, and an ^{unused}~~unused~~ identifier may be stored in the table when the code has expired.

20 In step S3043, the P-code use table in the server
is updated. More specifically, the newly assigned P-code
is stored, and the valid dates of the P-code are set at
the valid dates designated at the time of IP information
registration, or at a date after a predetermined period
25 (e.g., after three months) from the valid dates of the
IP information set by the information provider.

09547397 "041100

In this way, an IP P-code is issued. In issuing an IP P-code, the valid dates of the code are looked up. In extracting information corresponding to the designated IP P-code, it is checked whether the current
5 time falls within the range between the "date of start of insertion" and "valid dates of information", which are registered in the IP information registration table (Fig. 7) of the P-code.

In this example, to perform issue processing at a
10 high speed, a table as shown in Fig. 73 is prepared. However, since the valid dates of the code are registered in the IP information registration table shown in Fig. 7, a P-code may be issued by looking up this table. Additionally, for example, an IP code usable
15 in the server may be temporarily issued for information registration, and it may be determined whether the temporarily issued code can be used, by looking up the valid dates of the code registered in the IP information registration table. In this case, it is determined
20 whether the time (year, month, and day) of temporary code issue is before the valid dates of the code. If it is determined that the code has expired, issue of the IP code is inhibited, and temporary issue of another IP code and determination are repeated until an IP code is
25 finally issued.

The procedure of issuing a P-code for

advertisement information is basically the same as the procedure of issuing a P-code for IP information.

<Description of Various Services>

Details of information acquisition processing (to be referred to as an information service hereinafter) in step S116, mail data acquisition processing (to be referred to as a mail service hereinafter) in step S117, personal information acquisition processing (to be referred to as a personal information service hereinafter) in step S118, distribution data acquisition processing (to be referred to as a distribution service (reception of registered information) hereinafter) in step S119, and distribution information registration processing (to be referred to as a distribution service (registration of information) hereinafter) in step S123, and examples of display windows displayed on the touch panel 104 of the P service terminal 100 in executing each processing will be described next.

An initial window for executing the services will be described first with reference to Fig. 75.

Referring to Fig. 75, an initial window 2000 has buttons 2001 to 2004. To execute the information service, mail service, personal information service, or distribution service (reception of registered information), a P-code for executing the service is input using one of the buttons 2001 to 2003. The button

00110"041100
09547397

2001 is pressed to input a P-code using the touch panel
104. The button 2002 is pressed to input a P-code using
the portable terminal 400. The button 2003 is pressed to
input a P-code using the bar code reader 107. The button
5 2004 is pressed for the distribution service
(registration of information) (to be described later).

When the button 2001 in the initial window 2000 is
pressed, a window 2005 shown in Fig. 76 is displayed.

The window 2005 is a P-code input window in which
10 a P-code for executing various services including the
information service, mail service, distribution service
(reception of registered information), and personal
information service is input.

The window 2005 has a ten-key group 2006. A
15 desired P-code is input using the keys of the ten-key
group 2006. The input P-code is displayed in an area
2007. After the end of input, a button 2008 is pressed
to acknowledge the input P-code. To cancel the input
P-code, a button 2009 is pressed to delete the P-code
20 displayed in the area 2007. To correct the input P-code,
a button 2010 is pressed to correct the P-code to be
corrected using a cursor (not shown) on the area 2007. A
button 2011 is pressed to input a P-code associated with
foreign information.

25 When the button 2008 is pressed, the structure of
the input P-code is determined. On the basis of the

determination result, a window for executing various services including the information service, mail service, distribution service (reception of registered information), and personal information service or a
5 window 2012 shown in Fig. 77 is displayed. If the input P-code has expired, a window (not shown) for notifying the user of it is displayed.

The window 2012 shown in Fig. 77 has a ten-key group 2013 for inputting a password and buttons 2015 to
10 2017. In an area 2014, "*" is displayed as the password is input.

When the button 2015 is pressed after completion of password input, a window for executing various services including the information service, mail service,
15 distribution service (reception of registered information), and personal information service is displayed on the basis of the determination result of the structure of the P-code input in the window 2005 in Fig. 76. In this embodiment, a P-code input as a number
20 sequence hyphenated in units of four digits (in units of four numbers) is determined as a "nontelephone number" (IP P-code), and a P-code input as another type of number sequence (unhyphenated number sequence or a number sequence hyphenated in units of digits other than four
25 digits) is determined as a "telephone number" (personal P-code).

09547397-041100

When it is determined that the input P-code is "telephone number#Subcode", a window for executing the mail service is displayed. When the input P-code is "telephone number-Subcode", a window for executing the distribution service (reception of registered information) is displayed.

When the input P-code is "nontelephone number", a window for executing the information service is displayed.

When the input P-code is "telephone number##Subcode", a window for executing the personal information service is displayed.

When the button 2002 in the initial window 2000 shown in Fig. 75 is pressed, a window 2018 shown in Fig. 78 is displayed.

The window 2018 is a P-code input window by the portable terminal 400. After completion of input, when a button 2019 is pressed, the structure of the input P-code is determined. On the basis of the determination result, a window for executing various services including the information service, mail service, distribution service (reception of registered information), and personal information service or the window 2012 shown in Fig. 77 is displayed. To cancel the input P-code, a button 2020 is pressed. If the input P-code has expired, a window (not shown) for notifying

the user of it is displayed.

When the button 2003 in the initial window 2000 shown in Fig. 75 is pressed, a window 2021 shown in Fig. 79 is displayed.

5 The window 2021 is a P-code input window by the bar code reader 107. After completion of input, when a button 2022 is pressed, the structure of the input P-code is determined. On the basis of the determination result, a window for executing various services
10 including the information service, mail service, distribution service (reception of registered information), and personal information service or the window 2012 shown in Fig. 77 is displayed. To cancel the input P-code, a button 2023 is pressed. If the input
15 P-code has expired, a window (not shown) for notifying the user of it is displayed.

Windows displayed on the basis of the determination result of the structure of the input P-code will be described next.

20 A window for executing the information service, which is displayed when the input P-code is a nontelephone number, will be described first with reference to Fig. 80.

When the input P-code is an IP P-code, the
25 contents of information corresponding to the IP P-code are displayed in a window 2025. More specifically, in an

searched advertisement and information to be printed.
Advertisement search processing by the P service server
200 will be described later.

Next, a window for executing the mail service,
5 which is displayed when the input P-code is "telephone
number#Subcode", and a window for executing the
distribution service (reception of registered
information), which is displayed when the input P-code
is "telephone number-Subcode", will be described with
10 reference to Fig. 83.

In this embodiment, it is determined, by
identifying a predetermined symbol contained in the
P-code, whether the surfix portion attached to the
telephone number is "#Subcode", "-Subcode", or
15 "##Subcode", thereby determining the service to be
executed: the mail service, distribution service, or
personal information service. Instead, the type of
service to be executed may be determined by the P
service server 200 on the basis of the input personal
20 P-code by directly looking up the P-code table shown in
Figs. 10, 11, and 12, and on the basis of the
determination result, a window to be displayed (an
operation window associated with the service) may be
determined.

25 A window for executing the mail service will be
described with reference to Fig. 83.

0954397.041100

A window 2042 is a window for displaying the contents of user's mail corresponding to a personal P-code represented by the input P-code. More specifically, in an area 2046, the surfix (#n, n: 0, 1, 2,...) in an input P-code, the subject of mail corresponding to the P-code, sender, the number of pages, printing conditions (in this embodiment, color or monochrome printing and the presence/absence of printing can be particularly designated as printing conditions, for which buttons 2046a to 2046c are prepared) are displayed.

In an area 2047, the printing contents of mail to be printed in the area 2046 are displayed. In addition to this area, the button 2028a in the window 2025 shown in Fig. 80 may be displayed to allow the user to set insertion of an advertisement to the mail, or an appropriate advertisement for the mail to be printed may be searched by the P service server 200.

A button 2048 is pressed to display a print preview of mail to be printed. When the button 2048 is pressed, the window shown in Fig. 81 described above is displayed. A button 2049 is pressed to set print options for mail to be printed. When the button 2049 is pressed, a window shown in Fig. 84 is displayed to set print options. This window will be described later in detail. A button 2050 is pressed to print mail to be printed. A

options of mail to be printed. As shown in Fig. 84, an item group settable as print options (in this embodiment, "continuously print mail messages on one paper sheet" and "densely print with smallest letters") are displayed in the window 2053. The presence/absence of execution of each item can be designated by a button group 2054. A button 2055 is pressed to acknowledge the set print options. A button 2056 is pressed to cancel the set print options.

10 A window for executing the personal information service, which is displayed when the input P-code is "telephone number##Subcode", will be described next with reference to Fig. 85.

When the input P-code represents the personal information service, the contents of the personal information service are displayed in a window 2057. More specifically, in an area 2061, surfixes (##m, m: 0, 1, 2,...) in the input P-codes, contents of information corresponding to the P-codes, the number of pages, and buttons 2061a and 2061b for setting the presence/absence of printing are displayed.

In an area 2062, the print contents of information to be printed in the area 2061 are displayed.

An information group managed by a surfix (##m) is
25 called a frame.

A button 2063 is pressed to register a new frame

or change the contents of a registered frame. When the button 2063 is pressed, a window shown in Fig. 86, which is used to register/change information, is displayed. This window will be described later in detail. A button 5 2064 is pressed to display a print preview of a frame to be printed. A button 2065 is pressed to print a frame to be printed. A button 2066 is pressed to display the preceding window. A button 2067 is pressed to cancel contents set in the window 2057.

- 10 A button 2058 is pressed to print all frames managed by the P service server 200. A button 2059 is pressed to display, of frames out of the area 2061, the contents of frames with smaller surfix numbers. A button 2060 is pressed to display, of frames out of the area 15 2061, the contents of frames with larger surfix numbers.

In this embodiment, when the surfix number (##m) attached to the telephone number, i.e., the input P-code, is "0", frames corresponding to the surfix number are displayed ~~as many as possible~~, as shown in the area 2061.

- A 20 If the surfix has a number other than "0", a frame corresponding to a surfix matching the number is displayed.

When the button 2063 is pressed, a window 2068 shown in Fig. 86 is displayed.

- 25 The window 2068 has a ten-key group 2070 for designating a surfix (##m) to be registered or changed,

and an area 2071 for displaying the input surfix (##m).
Especially, to register a new frame, a button 2069 is
pressed. A button 2072 is pressed to acknowledge the
input surfix (##m). A button 2073 is pressed to cancel
5 the input surfix (##m). A button 2074 is pressed to
correct the input surfix (##m).

When the button 2072 or 2069 is pressed, a window
2075 shown in Fig. 87 is displayed.

The window 2075 is a window for displaying the
10 contents of an information group managed by a frame
corresponding to the surfix (##m) input to the area 2071.
More specifically, P-codes managed by the frame,
contents corresponding to the P-codes, and buttons 2078a
and 2078b for setting the presence/absence of
15 registration are displayed in an area 2078.

A button 2079 is pressed to register another
information (P-code) in this frame. When the button 2079
is pressed, the above-described window for registering a
P-code, shown in Fig. 76, is displayed. When the ten-key
20 group 2069 shown in Fig. 86 is pressed to register a new
frame, the area 2078 is blank because no information is
managed by the frame corresponding to the input surfix
(##m).

A button 2080 is pressed to acknowledge the
25 registered state of information of the frame to be
registered. A button 2081 is pressed to display the

preceding window. A button 2082 is pressed to cancel contents set in the window 2075.

When the button 2080 is pressed, a window 2083 shown in Fig. 88 is displayed.

5 The window 2083 is a window for setting the size of a paper sheet used to print a registered frame. In areas 2084, 2085, and 2086, the sizes of paper sheets usable for printing are displayed. When the user presses the area of a desired paper size, display of the pressed
10 area is inverted to notify the user of designation of the paper size. Buttons 2087 and 2088 are used to set the direction (landscape or portrait) of the paper sheet to be used. A button 2089 is pressed to acknowledge the designated size and direction of the paper sheet to be
15 used for printing. A button 2090 is pressed to display the preceding window. A button 2091 is pressed to cancel contents set in the window 2083.

Windows for executing the distribution service (registration of information) which is executed when the
20 button 2004 in the initial window 2000 shown in Fig. 75 is pressed will be described sequentially.

When the button 2004 in the initial window 2000 is pressed, a window 2092 shown in Fig. 89 is displayed.

The window 2092 is a P-code input window in which
25 a P-code (user's telephone number) for executing the distribution service (registration of information) is

input.

The window 2092 has a ten-key group 2093. A P-code is input using the keys of the ten-key group 2093. The input P-code is displayed in an area 2094. To
5 acknowledge the input P-code, a button 2095 is pressed. To cancel the input P-code, a button 2096 is pressed to erase the P-code displayed in the area 2094. To correct the input P-code, a button 2097 is pressed to correct the P-code to be corrected using a cursor (not shown) on
10 the area 2094. A button 2098 is pressed to input a foreign P-code.

When the button 2095 is pressed, a window 2099 shown in Fig. 90 is displayed. If the input P-code has expired, a window (not shown) for notifying the user of
15 it is displayed.

Constituent elements 2100 to 2104 in the window 2099 and functions thereof correspond to those of the constituent elements 2013 to 2017 in the window 2012 shown in Fig. 77, respectively, and a detailed
20 description thereof will be omitted.

When the button 2102 in the window 2099 shown in Fig. 90 is pressed, a window 2105 shown in Fig. 91 is displayed.

The window 2105 is a window for selecting an
25 information registration method in the distribution service (registration of information). A button 2106 is

pressed to register information using a scanner. A
button 2107 is pressed to register information using an
external device. When one of the buttons is pressed, a
window corresponding to the button is displayed. These
5 windows will be described later in detail. A button 2108
is pressed to display the preceding window. A button
2109 is pressed to cancel registration of information.

When the button 2106 is pressed, a window 2110
shown in Fig. 92 is displayed.

10 The window 2110 is a window for instructing the
user to set an original to be registered on the scanner
102. A button 2111 is pressed to execute an input
operation for the set original. When the button 2111 is
pressed, a window 2114 shown in Fig. 93 is displayed. A
15 button 2112 is pressed to display the preceding window.
A button 2113 is pressed to cancel the input operation
for the set original.

When the button 2107 in the window 2105 shown in
Fig. 91 is pressed, the same window as the dialog box
20 shown in Fig. 40 is displayed, so information can be
registered using an external device such as the disk
unit 108 or infrared communication section 105. When
information to be registered is designated, and "next"
is selected, the window 2114 shown in Fig. 93 is
25 displayed. The information to be registered can be
either an image or character information.

The window 2114 shown in Fig. 93 is a window for displaying a preview of information to be registered. In an area 2115, a preview of information to be registered is displayed. A button 2116 is pressed to display a preview of information next to the information that is currently being displayed. A button 2117 is pressed to register another information. When this button is pressed, the window shown in Fig. 91 is displayed. A button 2118 is pressed to cancel registration of the information displayed in the area 2115. A button 2119 is pressed to register the information displayed in the area 2115.

When the button 2119 is pressed, a window 2120 shown in Fig. 94 is displayed.

15 The window 2120 is a window for setting a password requested when another user prints the information to be registered. This window has a ten-key group 2121, and a desired password is input using the keys of the ten-key group 2121. As the password is input, the password is
20 displayed in an area 2122. After completion of input, to acknowledge the input password, a button 2123 is pressed. To cancel the input password, a button 2124 is pressed. To correct the input password, a button 2125 is pressed to correct the password to be corrected using a cursor
25 (not shown) on the area 2122.

When the button 2123 is pressed, a window 2126

shown in Fig. 95 is displayed.

The window 2126 is a window for setting the valid dates of the information to be registered. A button 2127 is pressed to validate the information until tomorrow. A
5 button 2128 is pressed to validate the information for one week. A button 2129 is pressed to validate the information for one month. A button 2130 is pressed to display the preceding window. A button 2131 is pressed to cancel setting of the valid dates of the information
10 to be registered.

A When one of the buttons 2127, 2128, ^{or}~~and~~ 2129 is pressed, a window 2132 shown in Fig. 96 is displayed.

The window 2132 is a window for causing the user to confirm the registered contents of the information to
15 be registered. More specifically, in an area 2133, the P-code, password, data amount, valid dates corresponding to the information to be registered are displayed. A button 2134 is pressed to acknowledge the registered contents of the information to be registered. A button
20 2135 is pressed to display the preceding window. A button 2136 is pressed to cancel the registered contents of the information to be registered. When the registered contents of the information to be registered are acknowledged, the number of registered data set in the
25 user information table shown in Fig. 9 for the distribution service is incremented by one, and the

P-code (P-code in the form of "telephone number-Subcode") attached to the registered information is added to the P-code list of the distribution service information. In addition, the information displayed in the area 2133 is registered in the distribution information P-code table shown in Fig. 11.

A window 2200 shown in Fig. 97 is displayed in accordance with the window displayed to execute various services including the information service, mail service, distribution service (reception of registered information), personal information service, and distribution service (registration of information).

The window 2200 is a window for selecting a settlement method for a charge generated when the information service, mail service, distribution service (reception of registered information), personal information service, or distribution service (registration of information) is executed. The charge is displayed at the lower left side of the window. The user presses a button 2201 to pay the charge in cash, a button 2202 to pay using a credit card, a button 2203 to pay by online settlement, a button 2204 to pay using a debit card, or a button 2205 to pay using a prepaid card. A window (not shown) necessary for settlement is displayed as one of the buttons is pressed.

A button 2206 is pressed to display the preceding

window. A button 2207 is pressed to cancel execution of selection of the settlement method.

09542397-041100
The above-described windows displayed to execute various services including the information service, mail
5 service, distribution service (reception of registered information), personal information service, and distribution service (registration of information) are examples of main windows displayed in executing
10 operation. In the process of operation, various windows including a window for causing the user to confirm displayed contents and a window for input are appropriately displayed.

Next, processing flows for executing various services including the information service, mail service,
15 distribution service (reception of registered information), personal information service, and distribution service (registration of information) will be described sequentially.

In the following processing flows, the P service
20 server 200 looks up the tables shown in Figs. 7 to 15 and transmits information corresponding to a P-code received from the P service terminal 100 or data (property data or preview image) necessary for the information to the P service terminal 100. In addition,
25 in accordance with data such as a print instruction for information corresponding to a P-code transmitted from

the P service terminal 100, the contents of the tables shown in Figs. 7 to 15 are updated.

A processing flow for executing the information service will be described first with reference to
5 Figs. 98A and 98B.

Fig. 98A is a flow chart showing a processing flow for executing the information service of this embodiment. Fig. 98B is a view showing the processing sequence in the service system for executing the information service
10 of this embodiment.

In step S2501, (1) the user acquires a P-code by the portable terminal 400. (2) The user moves to the P service terminal 100 while keeping the P-code stored in the portable terminal 400. (3) The P-code is input to
15 the P service terminal 100 (Figs. 75, 76, 78, and 79). (4) P service terminal 100 transmits the input P-code and the terminal properties (e.g., location of installation and printer performance) of the P service terminal 100 itself to the P service server 200.

20 In step S2502, (5) the P service server 200 acquires information corresponding to the received P service server 200. In step S2503, (6) the P service server 200 transmits the contents of the information, including the property data such as the service type,
25 preview image, and the number of pages, to the P service terminal 100. (7) The P service terminal 100 displays

the received contents of the information, including the property data, preview image, and the number of pages, on the touch panel 104 (Fig. 80). If a print preview or setting for advertisements is instructed, corresponding
5 windows (Figs. 81 and 82) are appropriately displayed to receive inputs from the user.

In step S2504, (8) it is determined whether printing of the displayed information is instructed. (9) If cancel of printing is instructed (NO in step S2504),
10 the P service terminal 100 transmits a message representing that cancel is instructed to the P service server 200, and processing is ended. On the other hand, (9) when printing is instructed (YES in step S2504), the P service terminal 100 requests the P service server 200
15 to prepare print data of the information corresponding to the P-code, and the flow advances to step S2505.

In step S2505, it is determined whether the information to be printed is charged for. (10) If the information is free (NO in step S2505), the flow
20 advances to the next processing. (11) If the information is charged for (YES in step S2505), the flow advances to step S2506 to receive the settlement method for settlement processing in printing from the user. (12) In accordance with the settlement method, the P service
25 terminal 100 and P service server 200 exchange necessary data (Fig. 97). The P service terminal 100 receives the

```
print data of the information to be printed from the P
service server 200 and prints the data.
```

A processing flow for executing the mail service will be described next with reference to Fig. 99A.

Fig. 99A is a flow chart showing a processing flow for executing the mail service of this embodiment. Fig. 99B is a view showing the processing sequence in the service system for executing the mail service of this embodiment. Assume that mail information to be output is transferred from the IP server (mail server) to the P service server in advance.

In step S2601, (1) the user acquires a P-code by the portable terminal 400. (2) The user moves to the P service terminal 100 while keeping the P-code stored in the portable terminal 400. (3) The user inputs the P-code to the P service terminal 100 (Figs. 75, 76, 78, and 79). (4) The P service terminal 100 transmits the input P-code and the terminal properties (e.g., location of installation and printer performance) of the P service terminal 100 itself to the P service server 200.

In step S2602, (5) when the P service server 200 recognizes that the received P-code is a P-code for the mail service, (6) the P service terminal 100 requests the user to input the password (Fig. 77). In step S2603, 25 (7) the password is confirmed. If the password is not correct (NO in step S2603), the user is requested to

re-input the password. However, if an incorrect password is input a plurality of number of times, processing is ended. If the password is correct (YES in step S2603), the flow advances to step S2604.

- 5 In step S2604, (8) the P service server 200 acquires mail corresponding to the received P-code. In step S2605, the P service server 200 transmits contents of the acquired mail, including property data (sender and subject), to the P service terminal 100. (9) The P
- 10 service terminal 100 displays the received contents of mail including the property data on the touch panel 104 (Fig. 83). If a print preview or option setting is instructed, corresponding windows (Fig. 81 and 84) are appropriately displayed to receive inputs from the user.
- 15 In step S2606, it is determined whether printing of the displayed mail is instructed. (11) If cancel of printing is instructed (NO in step S2606), the P service terminal 100 transmits a message representing that cancel is instructed to the P service server 200, and
- 20 processing is ended. On the other hand, (11) when printing is instructed (YES in step S2606), the P service terminal 100 requests the P service server 200 to prepare print data of the mail corresponding to the P-code, and the flow advances to step S2607.
- 25 In step S2607, it is determined whether the mail to be printed is charged for. (12) If the mail is free

(NO in step S2607), the flow advances to the next processing. (13) If the mail is charged for (YES in step S2607), the flow advances to step S2608 to receive the settlement method for settlement processing in printing
5 from the user. (14) In accordance with the settlement method, the P service terminal 100 and P service server 200 exchange necessary data (Fig. 97). In step S2609, the P service terminal 100 receives the print data of the mail to be printed from the P service server 200 and
10 prints the data. When printing is ended in step S2610, the printed mail information is automatically deleted from the P service server upon transmitting a print end notification to the P service server.

A processing flow for executing the distribution
15 service (reception of registered information) will be described with reference to Fig. 100A.

Fig. 100A is a flow chart showing a processing flow for executing the distribution service (reception of registered information) of this embodiment. Fig. 100B
20 is a view showing the processing sequence in the service system for executing the distribution service of this embodiment.

In step S2701, (1) the user acquires a P-code by the portable terminal 400. (2) The user moves to the P
25 service terminal 100 while keeping the P-code stored in the portable terminal 400. (3) The P-code is input to

the P service terminal 100 (Figs. 75 and 77 to 79). (4)
 The P service terminal 100 transmits the input P-code
 and the terminal properties (e.g., location and
 installation and printer performance) of the P service
 5 terminal 100 itself to the P service server 200.

In step S2702, (5) when the P service server 200
 recognizes that the received P-code is a P-code for the
 distribution service (reception of registered
 information), (6) the P service terminal 100 requests
 10 the user to input the password (Fig. 77). In step S2703,
 the password is confirmed. The password to be confirmed
 herein is a password set for individual distribution
 information. If the password is not correct (NO in step
 S2703), the user is requested to re-input the password.
 15 However, if an incorrect password is input a plurality
 of number of times, processing is ended. If the password
 is correct (YES in step S2703), the flow advances to
 step S2704.

In step S2704, (7) the P service server 200
 20 acquires information corresponding to the received
 P-code. In step S2705, the P service server 200
 transmits contents of the acquired information,
 including property data (information provider and
 subject), to the P service terminal 100. (8) The P
 25 service terminal 100 displays the received contents of
 information including the property data on the touch

Fig. 101A.

Fig. 101A is a flow chart showing a processing flow for executing the personal information service of this embodiment. Fig. 101B is a view showing the processing sequence in the service system for executing the personal information service of this embodiment.

In step S2801, (1) the user acquires a P-code by the portable terminal 400. (2) The user moves to the P service terminal 100 while keeping the P-code stored in the portable terminal 400. (3) The P-code is input to the P service terminal 100 (Figs. 75 and 77 to 79). (4) The P service terminal 100 transmits the input P-code and the terminal properties (e.g., location of installation and printer performance) of the P service terminal 100 itself to the P service server 200.

In step S2802, (5) when the P service server 200 recognizes that the received P-code is a P-code for the personal information service, (6) the P service terminal 100 requests the user to input the password (Fig. 77). In step S2803, the password is confirmed. If the password is not correct (NO in step S2803), the user is requested to re-input the password. However, if an incorrect password is input a plurality of number of times, processing is ended. If the password is correct (YES in step S2803), the flow advances to step S2804.

In step S2804, (7) the P service server 200

09547397-041100

acquires a frame corresponding to the received P-code.
In step S2805, (8) the P service server 200 transmits
contents of the acquired frame, including property data
(information provider and subject), to the P service
terminal ^{100, and} ~~100~~. (9) ^{the} ~~The~~ P service terminal 100 displays
the received contents of the frame including the
property data on the touch panel 104 (Fig. 85). When
registration of new information or a change in
registered information is instructed, corresponding
10 windows (Figs. 86 to 88) are appropriately displayed to
receive inputs from the user.

In step S2806, (10) it is determined whether
printing of the displayed frame is instructed. (11) If
cancel of printing is ^{instructed} ~~(NO in step S2806)~~, the P service
15 terminal 100 transmits a message representing that
cancel is instructed to the P service server 200, and
processing is ended. On the other hand, (11) when
printing is instructed (YES in step S2806), the P
service terminal 100 requests the P service server 200
20 to prepare print data of the frame corresponding to the
P-code, and the flow advances to step S2807. The print
data of the frame is generated from the registered
P-code list registered in the personal information
service P-code table shown in Fig. 12. Each P-code
25 registered in the registered P-code has been subjected
to group setting in this embodiment. For each P-code

subjected to group setting, P-code information having a maximum subcode of the attached section is acquired from the IP information table shown in Fig. 7. All the acquired P-code information have link information to

5 ^{another}~~another~~ P-code. Hence, information to be printed can be
acquired by searching for the P-code set as link
information again. If the date of registration of the
acquired information to be printed is before the final
date of printing set in the personal information service
10 P-code table shown in Fig. 12, it is regarded that this
information has been printed in the past, and therefore
the information is not printed. If all dates of
registration of individual information acquired from the
P-code list registered in the personal information
15 service P-code table are before the final date of
printing, a message (not shown) representing that no
information to be printed is present is displayed, and
processing is ended.

In step S2807, it is determined whether the frame
20 to be printed is charged for. (12) If the frame is free
(NO in step S2807), the flow advances to the next
processing. (13) If the frame is charged for (YES in
step S2807), the flow advances to step S2808 to receive
the settlement method for settlement processing in
25 printing from the user. (14) In accordance with the
settlement method, the P service terminal 100 and P

password (Fig. 90). If the input P-code is unregistered, password input is not requested. In step S2903, the password is confirmed. If the password is not correct (NO in step S2903), the user is requested to re-input
5 the password. However, if an incorrect password is input a plurality of number of times, processing is ended. If the password is correct (YES in step S2903), the flow advances to step S2904.

In step S2904, (4) the user inputs information to
10 be registered (Figs. 91 and 92). In step S2905, (5) the P service terminal 100 displays contents of the input information on the touch panel 104 (Fig. 93).

In step S2906, it is determined whether the displayed contents are acknowledged. If the contents are
15 not acknowledged (NO in step S2906), the flow returns to step S2904 to request the user to re-input the information. If the contents are acknowledged (YES in step S2906), (7) the P service terminal 100 transmits the input information and the property data of the
20 information, including the data type and the number of pages, to the P service server 200 and requests the P service server to issue a P-code. (8) In accordance with this request, the P service server 200 starts making a P-code correspond to the received information and the
25 property data of the information, including the data type and the number of pages. The user is requested to

input a password to be set for the input information
(Fig. 94).

In step S2908, (9) it is determined whether the
input password can be set. If the password cannot be set
5 (NO in step S2908), the flow returns to step S2907 to
request the user to re-input the password. If the
password can be set (YES in step S2908), the flow
advances to step S2909 to input the valid dates of the
input information (Fig. 95). In step S2910, (10) the P
10 service server registers the input information and the
password and valid dates therefor and issues a P-code
corresponding to the information. The P-code to be
issued has a combination of a numerical value
representing a "telephone number" and a numerical value
15 representing an "attached number (subcode)" and also has
a form of a number sequence, "telephone number-attached
number", with a predetermined symbol ("- " in this case)
inserted between the two numerical value sequences. The
attached number is 1 when the number of distribution
20 service information in the user information table shown
in Fig. 9 is 0. When the number of distribution service
information is not 0, pieces of registered distribution
service information searched are searched from the
P-code list, and the minimum attached number of a P-code
25 that has expired is used as an attached number. If a
registered distribution service information that has

expired is not present, "the number of distribution
service information + 1" is used as an attached number.
In step S2911, (11) the P service terminal 100 displays
the registered contents (P-code, password, data amount,
5 and valid dates) of the registered information on the
touch panel 104 (Fig. 96).

A Details of processing in ^{step}~~steps~~ S2502 in Fig. 98A,
step S2604 in Fig. 99A, step S2704 in Fig. 100A, and
step S2804 in Fig. 101A will be described with reference
10 to Figs. 103A and 103B.

<Procedure of Acquiring Information>

Figs. 103A and 103B are flow charts for explaining the procedure of acquiring IP information, mail data, and distribution data in the P service server 200 of this embodiment. First in step S3201, it is determined that the P-code input in the P service terminal 100 is an IP P-code. This can be determined on the basis of the state of the first bit of the P-code, as described above with reference to Figs. 17 and 18. When the P-code is an IP P-code, the flow advances to step S3202 to determine whether contents corresponding to the P-code are present in the P service server 200. This determination can be done by checking the state of the 17th bit, as shown in Fig. 18.

25 When the P service server 200 has the contents of
the IP information represented by the P-code, the flow

09547397-041100

advances from step S3202 to step S3203 to acquire the IP information and its properties in accordance with entity file information registered in the IP information registration table shown in Fig. 7.

5 If it is determined in step S3202 that the contents of the IP information are not present in the P service server 200 (i.e., the IP information has its contents on the IP server side), the flow advances to step S3204. In step S3204, the class category value and
10 external code are extracted from the input P-code. In this processing, the values of the 18th to 20th bits are extracted to obtain a class category value, and the external code section is extracted on the basis of the class category value. For example, when the class
15 category value is 3 (medium scale), the values of the 21st to 36th bits correspond to the external code, as shown in Fig. 18.

When the class category and external code are obtained in the above manner, a corresponding URL is
20 acquired by looking up the P-code use table (to be described later) shown in Fig. 72 in step S3205. The URL acquired at this time is the address of the IP server having the contents of the P-code. Hence, in step S3206, the IP server is accessed according to the URL obtained
25 in step S3205 to transmit the P-code. The IP server obtains contents and properties corresponding to the

provider rejects it. Processing of searching for advertisement information to be attached will be described below.

Fig. 104 is a flow chart of advertisement search
5 processing.

In step S3001, a keyword list of information of the information service or personal information service, mail of the mail service, or information of the distribution service is prepared for printing. This
10 keyword list is prepared in the following way in accordance with the contents of each service.

For the information service or personal information service, keywords are extracted by looking up the properties of IP information, properties of user
15 registration of the user, and properties of the P service terminal 100 for printing.

For the mail service, keywords are extracted by looking up the properties of user registration of the user and properties of the P service terminal 100 for
20 printing.

For the distribution service, keywords are extracted by looking up the properties of the P service terminal 100 for printing, and also the properties of user registration of the user when the user has done
25 user registration.

In any service, the keyword list can be prepared

in units of information. For example, for the information service, the keyword list of the properties of IP information, the keyword list of the properties of user registration, and the keyword list of the properties of the P service terminal 100 can be individually prepared. This will be described below in more detail by exemplifying the information service.

Figs. 105A to 105E are views showing examples of keyword lists for IP information.

10 For example, Fig. 105A shows a keyword list of IP
information requested by the user in the information
service. As a keyword, "marriage" is extracted. In
Fig. 105B, keywords are extracted from the registered
matters of user registration. In Fig. 105C, a keyword is
15 extracted from the properties (e.g., location of
installation) of the P service terminal.

Each keyword has a numerical value of "weight". This numerical value is given to each keyword in consideration of universally accepted idea on the basis of the contents and used to define priority of advertisement information in advertisement search processing. A numerical value with "+" means that IP information or the like including the keyword has positive contents when viewed from the universally accepted idea. A numerical value with "-" means that the information has negative contents. The magnitude of the

numerical value can be proportional to the degree of importance.

In the P service system, in addition to these keyword lists, a highest priority keyword list and
5 lowest priority keyword list set on the system side can be prepared.

The highest priority keyword list is a list of keywords corresponding to an advertisement that informs, e.g., a special campaign held on the P service system.
10 An example of this keyword list is shown in Fig. 105D.

The lowest priority keyword list is a list of keywords with which at least one advertisement information can be searched for and is prepared to prevent advertisement search processing from searching
15 no advertisement information. Hence, as a lowest priority keyword, a keyword having wide meaning is used.

In step S3002, using each keyword as a search key on the basis of the keyword lists prepared in step S3001, advertisement information having a keyword matching the
20 search keyword is searched for. In step S3003, the search result list is prepared.

Figs. 106A to 106E are examples of search result lists.

The search result lists are prepared in units of
25 the above-described five keyword lists.

Fig. 106A shows a search result list corresponding

to the keyword list of IP information (Fig. 105A), in which five pieces of advertisement information are searched for by the keyword "marriage". In this list, "weight" is a numerical value given to the keyword in each advertisement information and has the same meaning as the above-described "weight". The "degree of matching" is a numeral value obtained by multiplying the numerical value of "weight" of one keyword by that of the other keyword. More specifically, in the keyword list of IP information, since the weight of "marriage" is "+10", the columns of "degree of matching" in Fig. 106A are filled with results obtained by multiplying "+10" by each of weights "+10", "-5", "+3", "-4", and "+7" of the keywords of advertisement information.

In this advertisement search processing, an advertisement having a larger value of "degree of matching" has a higher priority of insertion. As the value becomes small, the priority becomes low.

20 As shown in Figs. 106A and 106B, a single keyword
has many weights. This is because advertisement
information including the keyword "marriage" may be an
advertisement of a wedding ceremony hall or an
advertisement of divorce consultation. If they are
25 regarded to be equivalent, inappropriate advertisement
information may be inserted into contents of information

to be printed.

09547397-041100

In processing of this embodiment, if negative advertisement information is searched for in correspondence with positive IP information, values with signs "+" and "-" are multiplied. The degree of matching has a negative value, and the priority can be made low. If negative advertisement information is searched for in correspondence with negative IP information (e.g., an advertisement of funeral and an advertisement of a hospital), values with signs "-" and "-" are multiplied. The degree of matching has a positive value, and the priority becomes high.

In step S3004, the pieces of advertisement information in the search result list are rearranged by looking up the properties of advertisement information.

In rearranging the pieces of information, on the basis of the properties of each advertisement information, a value is added to or subtracted from the degree of matching calculated in advance. For example, an advertisement whose term of insertion has expired or charge exceeds the maximum charge must not be inserted, and a predetermined numerical value can be subtracted from the calculated degree of matching. On the other hand, for an advertisement whose limitations on printing (designated in the dialog box shown in Fig. 65 or 66) are lenient, a predetermined numerical value can be

Figs. 107A to 107E, the degree of matching is not always proportional to the numerical value of "weight".

In step S3005, a layout example of advertisement information is prepared. A plurality of layout examples
5 are prepared by picking up pieces of advertisement information from the search result lists shown in Figs. 107A to 107E in descending order of priority.

Priorities may be defined in units of search result lists shown in Figs. 107A to 107E. For example,
10 first advertisement information may be picked up from the search result list of the highest priority list (Fig. 107D), and then pieces of advertisement information may be sequentially picked up from the search result list of IP information (Fig. 107A), the
15 search result list of user registration (Fig. 107B), the search result list of the P service terminal (Fig. 107C), and the search result list of the lowest priority list (Fig. 107E).

In step S3006, one layout example that is supposed
20 to be most appropriate is selected from the layout examples of advertisement information in consideration of the user's desire, print size, and total charge. The P-code and layout conditions of the advertisement information are specified and temporarily stored, and
25 advertisement search processing is ended.

<Operation of Portable Terminal>

The P-code extraction function and P-code transmission function of the portable terminal 400 according to this embodiment will be described next.

Fig. 108 is a flow chart for explaining P-code extraction processing of the portable terminal of this embodiment. This processing is executed when the contents of mail received are being displayed on the portable terminal 400.

In steps S3101 to S3103, it is determined whether the cursor keys 401 and 402 of the portable terminal 400 are operated, the block designation key 404 is operated, and the P-code key 403 is operated.

When the cursor key is operated in the mail displayed state, the flow advances from step S3101 to step S3105 to determine whether block designation is progressing. The block designation mode is set in step S3109 (to be described later) by operating the block designation key. If the block designation mode is not set, the flow advances to step S3106 to move the cursor in units of characters in the display of mail contents. If the block designation mode is set, a region where the cursor has moved is set as a selected region, and display of that portion is inverted. The flow advances to step S3104. If mail display continues, the flow returns to step S3101. If mail display is ended, this processing is ended.

When the block designation key 404 is operated,
the flow advances from step S3102 to step S3108 to
determine whether the block designation mode has already
been set. If NO in step S3108, the flow advances to step
5 S3109 to switch the operation mode to the block
designation mode. If YES in step S3108, the flow
advances to step S3110 to cancel the block designation
mode. That is, the block designation key functions as an
ON/OFF switch for the block designation mode. After that,
10 the flow advances to step S3104. If mail display
continues, the flow returns to step S3101. If mail
display is ended, this processing is ended.

When the P-code key 403 is operated, the flow
advances from step S3101 to step S3111 to determine
15 whether a selected region in inverted display is present
in the currently displayed character string. If YES in
step S3111, the flow advances to step S3112 to store the
selected region in the P-code storage area 422c. If NO
in step S3111, the flow advances to step S3113 to
20 automatically select a P-code. After that, the flow
advances to step S3104. If mail display continues, the
flow returns to step S3101. If mail display is ended,
this processing is ended.

Automatic P-code extraction in step S3113 will be
25 described. Fig. 109 is a flow chart for explaining
automatic P-code extraction processing in step S3113.

In step S3120, a character string enclosed by two tags <Pcode> and </Pcode> is searched for. When a character string enclosed by the two tags <Pcode> and </Pcode> is searched for, the flow advances from step
5 S3121 to step S3122 to store the detected character string in the P-code storage area 422c. This processing is executed for the entire mail that is being displayed currently (step S3123).

An operation mode for executing the above
10 processing for all mail data held in the memory of the portable terminal 400 at once may be provided.

In the above way, the portable terminal 400 of this embodiment can store a P-code sent as mail in the P-code storage area 422c. Even when the user is notified
15 of a P-code not by electronic data such as mail but by a magazine or newspaper, the P-code may be input using the P-code key and dial keys and held in the P-code storage area 422c. According to the portable terminal 400 of this embodiment, the P-code stored in the P-code storage
20 area 422c can be input to the P service terminal 100 by communication with the P service terminal 100.

Fig. 110 is a flow chart for explaining P-code transmission processing by the portable terminal of this embodiment. This processing is executed when the
25 displayed contents of the portable terminal 400 are in the initial state.

In step S3141, when operation of the P-code key 403 is detected, the flow advances to step S3142 to determine whether a P-code is stored in the P-code storage area 422c. If no P-code is stored in the P-code storage area 422c, the flow advances to step S3143 to display a message representing that no P-code is present on the display 410, and this processing is ended.

If YES in step S3142, the flow advances to step S3144 to start communication processing with the P service terminal 100 using the infrared communication section 405. It is determined in step S3145 whether the P service terminal 100 is ready, and processing waits until the P service terminal 100 is ready. If the wait time exceeds a predetermined time, it is determined that time is out. The flow advances from step S3146 to step S3147 to display a message representing a communication error on the display 410, and processing is ended.

When it is confirmed that the P service terminal 100 is ready, the P-code stored in the P-code storage area 422c is transmitted to the P service terminal 100 in step S3148.

When transmission is ended, it is inquired on the display 410 whether the P-code currently stored in the P-code storage area 422c is to be erased. If the user instructs to erase the P-code, the P-code is erased in step S3151.

The above processing can also be applied to a case wherein the portable terminal 400 is connected to the portable terminal connector 106 of the P service terminal 100.

5 In the above processing, transmission is started by the key operation of the portable terminal 400. Instead, a P-code may be automatically input to the P service terminal 100 under the control of the P service terminal 100 without operating any keys on the portable terminal side. Fig. 111 is a flow chart for explaining another form of P-code transmission processing by the portable terminal of this embodiment.

In step S3161, when it is detected that the portable terminal is connected to the portable terminal connector 106 (or when a predetermined signal is sent to the P service terminal through the infrared communication section by operating the P-code key), communication between the P service terminal and the portable terminal starts in step S3162.

20 When a P-code request is input from the P service terminal 100 by communication, the flow advances from step S3163 to step S3165 to determine whether a P-code is stored in the P-code storage area 422c. If no P-code is stored, the flow advances to step S3167 to notify the P service terminal ¹⁰⁰~~10~~ that no P-code is present. If a P-code is present in the P-code storage area 422c, the

flow advances to step S3166 to transmit the stored
P-code to the P service terminal 100.

The subsequent processing in steps S3168 to S3170
is the same as the above-described processing in steps
5 S3149 to S3151.

As described above, according to the portable
terminal of this embodiment, a P-code can be extracted
from mail, held in the memory, and transmitted to the P
service terminal. Hence, any input error in operation of
10 the P service terminal 100 can be prevented, and the
operability is largely improved.

<Other Embodiment>

The present invention may be applied to a system
constituted by a plurality of devices (e.g., a host
15 computer, an interface device, a reader, a printer, and
the like) or an apparatus comprising a single device
(e.g., a copying machine, a facsimile apparatus, or the
like).

The object of the present invention is realized
20 even by supplying a storage medium storing software
program codes for realizing the functions of the
above-described embodiment to a system or apparatus, and
causing the computer (or a CPU or an MPU) of the system
or apparatus to read out and execute the program codes
25 stored in the storage medium.

In this case, the program codes read out from the

storage medium realize the functions of the above-described embodiment by themselves, and the storage medium storing the program codes constitutes the present invention.

5 As a storage medium for supplying the program codes, a floppy disk, a hard disk, an optical disk, a magnetooptical disk, a CD-ROM, a CD-R, a magnetic tape, a nonvolatile memory card, a ROM, or the like can be used.

10 The functions of the above-described embodiment are realized not only when the readout program codes are executed by the computer but also when the OS (Operating System) running on the computer performs part or all of actual processing on the basis of the instructions of the program codes.

15 The functions of the above-described embodiment are also realized when the program codes read out from the storage medium are written in the memory of a function expansion board inserted into the computer or a function expansion unit connected to the computer, and the CPU of
20 the function expansion board or function expansion unit performs part or all of ^{the} actual processing on the basis of
A the instructions of the program codes.

 As many apparently widely different embodiments of the present invention can be made without departing from
25 the spirit and scope thereof, it is to be understood that the invention is not limited to the specific embodiments

thereof except as defined in the appended claims.

00T40" 26E/450